

# RoofPaint

Roof Coating

## Quick Guide:

- Weatherproof
- Extremely Durable & Hardwearing
- UV resistant
- Waterproof

A tough, thermoplastic, textured, weatherproof coating. Contains Mica and silica for maximum film protection against ultra-violet light and weather abrasion. Supplied ready for use. Application by brush or roller.

## SABS

An SABS 2000 hour artificial weathering test report is available on request.

## Storage

Can be stored, unopened, for 12 months. Protect from freezing.

## Surface preparation

### Old corrugated iron roofs

Wire brush surface and flush thoroughly using clean water.

### New corrugated iron roofs

Should be at least 12 months old before painting. Alternatively, a commercial galvanized cleaner could be used to remove all oils. Once surface is clean, apply 1 good coat of Bitumen Primer and allow to dry for 24 hours. Apply first coat of RoofPaint. Leave to dry for 6 hours. Apply a second coat of RoofPaint, ensuring that the Bitumen Primer is completely covered.

### Cement tile roofs

Organic growths should be removed by brushing with a solution of 1 volume household bleach (sodium hyperchlorite) solution and 3 volumes water. Allow 12 hours to kill spores then remove with a wire brush and water. Flaking, friable, chalking and soft surfaces must be scraped and wire-brushed to a firm foundation before priming with a solution of 1 volume CemBond and 4 volumes water. A small amount of RoofPaint, say one half part, can be incorporated in the priming coat for tinting purposes. Cracks and voids to be filled with Cemcrete Crack Filler, sanded level and re-primed with the CemBond solution.

## Mixing

Stir well before use. A little water may be added if necessary.

## Application

Application is by brush or lambs wool roller. Apply one good coat using an oval paintbrush or sheepskin roller. Leave to dry for 6 hours. Apply a second coat. Wash brushes and rollers with clean water.

## Coverage

Approximately 3 to 6m<sup>2</sup>/litre/coat.

## Packaging

Supplied in 5 litre and 20 litre non-returnable drums.

Apricot

Charcoal

Clay

Cocoa

Concrete Grey

Corn

Cream

Green

Ivory

Jasmine

Mushroom

Oyster Pink

Slate

Straw

Terracotta

White

