


























marmoleum® REAL_PRODUCT DATA_

ITEM

	Total Thickness		2.0mm (REAL / FRESCO) 2.5mm (REAL / FRESCO / VIVACE / STRIATO / CONCRETE / WALTON UNI)
	Wear Layer Thickness		2.0mm: 1.0mm 2.5mm: 1.5mm
	Dimensions		Rolls: 2m X 30-32m
	Dimensions (Welding Rod)		± Ø4.3mm X 50m
	Packaging		Rolls: 60 - 64m ² Per Roll
	Total Weight		2.0mm: 2.3 kg/m ² 2.5mm: 2.9 kg/m ²
	Colour Range		58 Selected Colours
	Use Classification	EN 685	2.0mm: CLASS 32 2.5mm: CLASS 34 2.0mm: CLASS 41 2.5mm: CLASS 42
	Reaction To Fire	EN ISO 13501-1	Cfl - S1
	Flexibility	ISO 24344 (EN 435)	2.0mm: Ø30mm 2.5mm: Ø40mm
	Castor Wheel Test	ISO 4918 (EN 425)	PASS SR*
	Residual Indentation	ISO 24343-1 (EN 433)	2.0mm: 0.07mm 2.5mm: 0.08mm
	Slip Resistance	DIN 51130 (EN 13036-4) EN 13893	R9 CLASS DS (u ≥0.30)
	Bacteriostatic		Marmoleum has fungistatic and bacteriostatic treatments
	Stain Resistance	EN 423 (ISO 26987)	PASS SR*
	Burn Mark Resistance		RESISTANT
	Static Electrical Charge	EN 1815	< 2kV
	Light Fastness	EN ISO 105-B02	>LEVEL 6
	Thermal Resistance	EN 12524	0.17 W/(m.K)
	Underfloor Heating	DIN 51130	Suitable provided that the temperature of the surface of the sub-floor does not exceed 27°C
	Sound Absorption	EN ISO 717-2	2.0mm: ΔLw = 6dB 2.5mm: ΔLw = 7dB
	Surface Treatment		Topshield 2
	Emissions	EN ISO 16000	< 100µg/m ³
	CE Conformity	EN 14041	PASS SR*
	Reach	1907/2006/CE	COMPLIANT

SR* = Standard Requirements

Available in half rolls subject to a cutting surcharge (ex-stock items only). A surcharge will be levied on quantities less than 200m² unless product is available ex-stock.

It is advised to confirm stock availability on 0860 346 679.