The door with the core that offers you more protection



Now you can get fire protection with the added benefit of acoustic insulation from one door. Trucore fire rated doors are manufactured for a guaranteed and proven 30 minute fire protection and up to 34DB sound insulation making it the obvious and most economical choice. Trucore 30 minute fire rated doors are manufactured from a tubular particle board core of 354kgs/m3.

TRUCORE PYROCOUST 30 MINUTE FIRE DOORS ARE IDEAL FOR:

Industrial Commercial Residential

TRUCORE PYROCOUST 30 MINUTE FIRE DOORS FEATURE:

- 33 RH Engineered Fire Rated Tubular Core
- Including the necessary intumescent
- Engineered Fire Rated Tubular Core
- Sound Insulation of up to 28 DB without special acoustic seal
- Sound Insulation of up to 34 DB with special acoustic seal
- Face finishes suitable for painting or specified custom timber veneers
- · Thickness precision
- Light weight construction but heavy duty stability
- Environmentally Friendly
- PEFC Certified


Test reports available on request




ADDED ACOUSTIC PERFORMANCE

The inclusion of retro fit seals increases the acoustic performance by 6DB

PLAN VIEW OF DOOR SEALS



Section through height of door



Trucore Pyrocoust fire resistant and acoustic doors can be supplied hung in and including a timber / steel door frame or as a leaf only.

Available in single or double leaf.



Durban Head Office, Export and Manufacturing Plant

Unit 2, 22 Brickworks Way, Briardene, Durban PO Box 40220, Redhill, 4071 Tel: 031-573 7380 Fax: 031-573 7381

Gauteng Sales and Service

Tel: 082 652 7667

Trucore Pyrocoust 30 minute Fire Doors