

geyser drip trays







EXTREMELY DURABLE



## product features

- The KwikTray Geyser Drip Tray is manufactured from recycled polyethylene and is extremely durable, lightweight and will not rust or dent.
- The Drip tray has been designed to discharge any water that is captured by the tray, through the waste outlet.
- Trays are supplied with a 50mm PVC adaptor, for connecting the waste pipe to the tray (Code DRT-FITT). The adaptor is parralel (not angled) to the tray for easy installation.

Horizontal & Vertical 50lt.100lt.150lt.200lt and 250lt

Horizontal 100lt

Horizontal 150lt and 200lt

Horizontal 250lt and 300 lt

Balanced cold water

to all cold water taps

Expansion drain to exterior of building

Pressure Cont

rol Valve

Vacuum breaker

• Trays are available for horizontal and vertical geyser installations.

## product specification data

The Kwikot KwikTray complies to SANS 11848 Drip Tray Specifications and forms part of SANS 10254 Geyser Installation Specification.

DRT600

DRT1200

DRT1600

DRT2100

## installation specification data

## Horizontal Geyser Installation (roof truss mounting)

With a horizontal geyser installation, the horizontal KwikTray format is to be used and the correct size tray must be installed for the corresponding geyser capacity (refer to table).

The drip tray must be installed in the following manner:

- It must be placed on the tie beams over a load-bearing wall and supported by timber that complies with at least grade 5 SANS 1783-2 and of a size at least 114mm x 50mm, spaced not more than 500mm apart.
- It must be sloped to the outlet end and rigidly maintained in that position.
- The 50mm PVC Adaptor must be fitted to the waist outlet on the tray. A 50mm PVC pipe is to be attached and piped from the drip tray and discharged to the outside of the building in a visible position.

The geyser is to be placed horizontally inside the tray. The Vacuum Breakers, Drain Cock and Safety Valve must be within the overall confines of the geyser tray dimensions, so that any water leakage is captured by the drip tray. Should the pressure control valve be installed in the roof, the same applies.

## Vertical Geyser Installation (cupboard mounting)

With a vertical geyser installation the vertical KwikTray format must be used. The tray is positioned directly underneath the vertical geyser installation.

The drip tray is to be installed in the following manner:

- Steel brackets to be used if wall mounted.
- Not to be attached to the geyser in any manner.
- Be suitably spaced to ensure that the drip tray does not become warped when filled half with water.
- It must be sloped to the outlet end and rigidly maintained in that position.
- the 50mm PVC adaptor must be fitted to the waste outlet on the tray and discharged to the outside of the building in a visible position.

The Vacuum Breakers, Drain Cock and Safety Valve must be within the overall confines of the geyser dimensions, so that any water leakage is captured by the drip tray. Should the pressure control valve be installed in a cupboard. the same applies.

## product warranty

Kwikot KwikTrays carry a one year guarantee from date of installation.

## kwikot branch contact details:

#### kwikot (pty) Itd inland division

PO Box 1016, Benoni, 1500 Tel: (011) 897 4600

#### **Domestic Sales**

email: sales.inland@kwikot.com AFTER SALES SERVICE TEL: 0861 KWIKOT (594568)

**Export Sales:** email: sales.export@kwikot.com

email: marketing.info@kwikot.com

Marketing:

Technical: email: technical.info@kwikot.com

### kwikot (pty) Itd eastern cape division

PO Box 29142, Sunridge Park, Port Elizabeth, 6008 Tel: (041) 399 4000 Fax: (041) 367 1005

## Domestic Sales

Email: sales.easterncape@kwikot.com

#### kwikot (pty) Itd western cape division

PO Box 32072, Ottery, Cape Town, 7808 Tel: (021) 690 2700 Fax: (021) 690 2800

#### **Domestic Sales**

Email: sales.westerncape@kwikot.com

# Balanced hot water to all hot Balanced cold ater pressu to all cold water taps exterior of building

Vacuum breaker

600 x 600

1200 x 600

1600 x 600

2100 x 600

Balanced hot water to all hot water taps

Safety valve piped to exterior of building

Vacuum breaker

Safety valve piped to exterior of building

Vacuum breaker

#### kwikot (pty) Itd kwazulu-natal division

P O Box 47366, Greyville, Durban, 4023 Tel: (031) 574 8700

#### Fax: (031) 574 8750 **Domestic Sales**

email: sales.kwazulunatal@kwikot.com