

ACT ALCHEMY COLOURANTS

PRODUCT CODE: ACT Range

TECHNICAL DATA SHEET

Product description	A range of Alchemy Colourants .	
Intended Uses	<ul style="list-style-type: none"> These colourants are balanced and allow a distributor to tint Alkyd based coatings and Quick Drying Alkyd using the Alchemy tinting system. 	
Features & Benefits	<ul style="list-style-type: none"> Strength controlled colourants Compatibility with a wide range of alkyd based coatings. Does not affect the performance properties of the tinted products 	
Product Information	Product Range / Colours	White (ACT 3201), Black (ACT 3120), Bright Red (ACT 3229), Red Oxide (ACT 3227), Bright Yellow (ACT 3331), Maroon Oxide (ACT 3123), Yellow Oxide (ACT 3222), Orange Oxide (ACT 3233), Green (ACT 3125), Blue (ACT 3321), Violet (ACT 3232), Ultramarine Blue (ACT 3230), Orange (ACT 3228), Mid Yellow (ACT 3226), Yellow 2 (ACT 3234) and Yellow 3 (ACT 3235).
	Viscosity at 23°C	60 – 115 KU (specific to different colours)
	Specific Gravity at 23°C	0.90 - 1.7 kg/L (specific to different colours)
Application Details	Mix product thoroughly before using. Add to the paint and stir until a homogenous colour is obtained.	
Storage & Packaging	Store away from direct sun, heat and severe cold. Packaging: 5L	
Safety Precautions	<ul style="list-style-type: none"> Always keep out of reach of children. Ensure good ventilation during application and drying. Do not smoke while painting. Flammable. Store in a cool dry place away from heat and sparks. In case of skin contact, wash with soap and water or a recognised skin cleaner. Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist. Harmful if swallowed. Do not induce vomiting. Seek medical attention. Refer to Safety Data Sheet for complete information. 	

DISCLAIMER:

The recommendations contained herein are given in all good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

N.B. Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

N.B. TO ORDER: Quote product name, product code number, packaging and colour.

KANSAI PLASCON (PTY) LIMITED

10 Frederick Cooper Drive,
 Factoria, Krugersdorp
 South Africa
 1739.
 Tel: +27 11 951 4500
 Fax: +27 800 110 932

PLASCON ADVISORY SERVICE: 0860 20 40 60

EMAIL: advice@kansaiplascon.co.za