

IAC ALCHEMY COLOURANTS

PRODUCT CODE: IAC RANGE

TECHNICAL DATA SHEET

Product Description	<ul style="list-style-type: none"> A range of Industrial Alchemy Colourants. 	
Intended Uses	These colourants are balanced and allow a distributor to tint Alkyd based coatings and Quick Drying Enamel using the Alchemy tinting system.	
Features & Benefits	<ul style="list-style-type: none"> Strength controlled colourants Compatibility with a wide range of alkyd-based coatings. Does not affect the performance properties of the tinted products. 	
Product Information	Product Range / Colours	White (IAC 2201), Black (IAC 2120), Bright Red (IAC 2229), Red Oxide (IAC 2227), Lemon Chrome (IAC 2331), Maroon Oxide (IAC 2123), Yellow Oxide (IAC 2222), Phthalo Green (IAC 2125), Phthalo Blue (IAC 2321), Violet (IAC 2232), Ultra Blue (IAC 2230), Scarlet Chrome (IAC 2228), Mid Chrome (IAC 2226).
	Viscosity at 23 °C	60 – 115 KU (specific to different colours)
	Specific Gravity at 23 °C	0.90 - 1.7 kg/L
Application	Mix product thoroughly before using. Add to the paint and stir until a homogenous colour is obtained.	
Storage and Packaging	Store away from direct sun, heat and severe cold.	
	Packaging: 5 L	
Safety Precautions	<ul style="list-style-type: none"> Always keep out of reach of children. Ensure good ventilation during application and drying. Do not smoke while painting. Flammable. Store in a cool dry place away from heat and sparks. In case of skin contact, wash with soap and water or a recognised skin cleaner. Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist. Harmful if swallowed. Do not induce vomiting. Seek medical attention. Refer to Safety Data Sheet for complete information. 	

DISCLAIMER:

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

NB: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging and colour.

KANSAI PLASCON (PTY) LTD

10 Frederick Cooper Drive,
Fatoria, Krugersdorp
South Africa
1739.

Tel: +27 11 951 4500

Fax: +27 800 110 932

PLASCON ADVISORY SERVICE: 0860 20 40 60

EMAIL: advice@kansaiplascon.co.za