

## CATALYST FOR EPIWASH CHROMATE FREE PRIMER (AW 1255)

PRODUCT CODE: KAT 1255

### TECHNICAL DATA SHEET

|                              |  |   |
|------------------------------|--|---|
| <b>Product Description</b>   | <b>KAT 1255</b> is a pigmented epoxy resin solution  |   |
| <b>Intended Uses</b>         | Used to catalyse the <b>EPIWASH CHROMATE FREE PRIMER (AW 1255)</b>   |   |
| <b>Product Information</b>   | Colour   | Pale Yellow   |
|                              | Specific Gravity   | 1.09  |
|                              | Pot life   | Dependent on temperature  |
| <b>Application Details</b>   | Mixing   | Mixing ratio: 1 part of <b>EPIWASH CHROMATE FREE PRIMER (AW 1255)</b> and 1 part <b>KAT 1255</b> by volume. |
| <b>Storage and Packaging</b> | Should be stored indoors in the original, unopened and undamaged container, in a dry place at a temperature not exceeding 30 °C.<br>Exposure to direct sunlight should be avoided.   |   |
| <b>Cautions</b>              | <ul style="list-style-type: none"> <li>• This material is flammable</li> <li>• Do not inhale vapours</li> </ul>  |   |
| <b>Safety Precautions</b>    | <ul style="list-style-type: none"> <li>• Keep out of reach of children.</li> <li>• Ensure good ventilation during application and drying.</li> <li>• In case of skin contact, wash with soap and water or a recognised skin cleaner.</li> <li>• Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist.</li> <li>• Harmful if swallowed. Do not induce vomiting. Seek medical attention.</li> <li>• Do not smoke while painting.</li> <li>• Flammable. Store in a cool dry place away from heat and sparks.</li> <li>• Refer to Safety Data Sheet for complete information</li> </ul> |   |

#### DISCLAIMER:

The recommendations contained herein are given in all good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

NB: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

**NB: TO ORDER: Quote product name, product code number, packaging and colour**

#### **KANSAI PLASCON (PTY) LIMITED**

10 Frederick Cooper Drive,  
Factoria, Krugersdorp  
South Africa  
1739.  
Tel: +27 11 951 4500  
Fax: +27 800 110 932

**PLASCON ADVISORY SERVICE:** 0860 20 40 60

**EMAIL:** advice@kansaiplascon.co.za