

CATALYST FOR STRONTIUM CHROMATE EPOXY PRIMER

PRODUCT CODE: KAT 508

TECHNICAL DATA SHEET

Product Description	KAT 508 is a pigmented epoxy resin solution	
Intended Uses	Used to catalyze the STRONTIUM CHROMATE EPOXY PRIMER (AW 255)	
Product Information	Colour	Pale Yellow
	Specific Gravity	1.13
	Pot life	Dependent on temperature
Application Details	Mixing	Mixing ratio: 1 part of STRONTIUM CHROMATE EPOXY PRIMER (AW 255) and 1 part KAT 508 by volume.
Storage and Packaging	Should be stored indoors in the original, unopened and undamaged container, in a dry place at a temperature not exceeding 30 °C. Exposure to direct sunlight should be avoided.	
Cautions	<ul style="list-style-type: none"> • This material is flammable • Do not inhale vapours 	
Safety Precautions	<ul style="list-style-type: none"> • Keep out of reach of children. • Ensure good ventilation during application and drying. • In case of skin contact, wash with soap and water or a recognised skin cleaner. • Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist. • Harmful if swallowed. Do not induce vomiting. Seek medical attention. • Do not smoke while painting. • Flammable. Store in a cool dry place away from heat and sparks. • Refer to Safety Data Sheet for complete information 	

DISCLAIMER:

The recommendations contained herein are given in all good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

NB: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging and colour

KANSAI PLASCON (PTY) LIMITED

10 Frederick Cooper Drive,
Factoria, Krugersdorp
South Africa
1739.
Tel: +27 11 951 4500
Fax: +27 800 110 932

PLASCON ADVISORY SERVICE: 0860 20 40 60

EMAIL: advice@kansaiplascon.co.za