



HARDENER FOR COLDCURE SCREED ROAD MARKING PAINT

PRODUCT CODE: STH 1

TECHNICAL DATA SHEET

| | | |
|--------------------------------|---|--|
| Product Description | Di-benzoyl peroxide powder hardener | |
| Intended Uses | Used to catalyse STP 1 & 2 COLD CURE SCREED ROAD MARKING PAINT . | |
| Product Information | Appearance | White free-flowing powder |
| | Solubility | Insoluble in water |
| | Peroxide content | Approx. 50% w/w |
| | Pot life | 15 mins @ 23°C |
| Application Details | Mixing | Mixing ratio: 100 parts STP 1 & 2 to 1 part STH 1 HARDENER by mass |
| Storage & Packaging | Store away from Base (STP 1&2) | |
| | Store away from direct sunlight ($\geq 30^{\circ}\text{C}$) | |
| | Packaging: 100g | |
| Cautions | <ul style="list-style-type: none">Not recommended for friable slurry surfaces | |
| Safety Precautions | <ul style="list-style-type: none">Keep out of reach of children.Ensure good ventilation during application and drying.Avoid skin contact. If accidental contact with skin should occur, wash immediately with soap and water or a recognised skin cleaner.Take care to avoid contact with the eyes. In case of contact, immediately rinse the eyes with plenty of water and seek medical attention.Harmful if swallowed. Seek medical attention and do not induce vomiting.Do not smoke while painting.Refer to Safety Data Sheet for complete information. | |

DISCLAIMER:

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

N.B. Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging and colour.

KANSAI PLASCON (PTY) LIMITED

10 Frederick Cooper Drive,
Factoria, Krugersdorp
South Africa
1739.

Tel: +27 11 951 4500

Fax: +27 800 110 932

PLASCON ADVISORY SERVICE: 0860 20 40 60

EMAIL: advice@kansaiplascon.co.za

