

POLYURETHANE ACRYLIC THINNER

PRODUCT CODE: SAT 354

TECHNICAL DATA SHEET

Product Description	Polyurethane Acrylic Thinner	
Intended Uses	Diluting of Transnet Solvent Based Polyurethane Range as well as Plascothane Enamel (UP Series)	
Features & Benefits	<ul style="list-style-type: none"> Formulated for Transnet application environment Meets requirements for CSS 183/2.60/1990 Balanced evaporation profile 	
Product Information	Appearance:	Liquid
	Colour:	Clear
	S G	0,87-0,91
	Flash Point:	< 23 °C
Storage and Packaging	Store in a cool place away from direct sunlight. Keep away from sources of ignition, open flames and sparks Packaging: 5 L	
Safety Precautions	<ul style="list-style-type: none"> Always keep solvent out of reach of children Ensure good ventilation during handling. If accidental contact with skin should occur, wash immediately with soap and water or a recognised skin cleaner. Take care to avoid contact with the eyes. In case of contact, immediately rinse the eyes with plenty of water and seek medical attention. Harmful if swallowed or inhaled. Seek medical attention and do not induce vomiting. Do not smoke while handling. Highly flammable. Store in a cool dry place away from heat and sparks. Refer to Safety Data Sheet for complete information. 	

DISCLAIMER:

The recommendations contained herein are given in all good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

N.B. Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

N.B. TO ORDER: Quote product name, product code number, packaging and colour.

KANSAI PLASCON (PTY) LTD

10 Frederick Cooper Drive,
Fatoria, Krugersdorp
South Africa
1739.
Tel: +27 11 951 4500
Fax: +27 800 110 932

PLASCON ADVISORY SERVICE: 0860 20 40 60

EMAIL: advice@kansaiplascon.co.za