

EPOXY THINNER

PRODUCT CODE: SAT 355

TECHNICAL DATA SHEET

Product Description	A formulated blend of solvents.	
Intended Uses	Used to thin epoxy products, specifically RUST INHIBITIVE EPOXY PRIMER (SAT 356) .	
Product Information	Appearance	Colourless liquid
	Type	Solvent blend
	S G at 23 °C	0,82 kg / L (typical)
	Flash Point	6 °C (typical Closed Cup)
Application Details	Mixing	Thin to 20 - 25 seconds Ford Cup No. 4 for SAT 356 or as specified.
Storage and Packaging	Store away from direct sun, open flames, sparks and severe cold.	
	Packaging: 5 L	
Cautions	<ul style="list-style-type: none"> • Use only for thinning of Epoxy Products 	
Safety	<ul style="list-style-type: none"> • Flammable - Keep away from source of ignition, flames, sparks and heat. • Use only in well ventilated environments. • Do not smoke during use. • Keep out of reach of children. • Dangerous if swallowed. Seek medical attention immediately. Do not induce vomiting. • Avoid contact with skin and eyes. • Do not dispose of into natural water-ways or drainage system. • Refer to Safety Data Sheet for complete information 	
Precautions		

DISCLAIMER:

The recommendations contained herein are given in all good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

N.B: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging and colour.

KANSAI PLASCON (PTY) LTD

10 Frederick Cooper Drive,
Factoria, Krugersdorp
South Africa
1739.

Tel: +27 11 951 4500

Fax: +27 800 110 932

PLASCON ADVISORY SERVICE: 0860 20 40 60

EMAIL: advice@kansaiplascon.co.za