

## PLASCON WOOD STOPPINGS

**PRODUCT CODE: BS Series**

### TECHNICAL DATA SHEET

<b>Product Description</b>	Wood Stoppings are waterbased putty like fillers.	
<b>Intended Uses</b>	Use to fill minor, shallow imperfections in solid timber and veneers For use on all interior wooden furniture and panelling such as Solid wood, Veneered chipboard and MD	
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"> <li>• Can be used as a wood stopper, grain filler.</li> <li>• Good adhesion and sandability</li> </ul>	
<b>Product Information:</b>	Colour	Available in a range of natural timber colours
	Viscosity	Putty
	Flammability	Not flammable
<b>Application Details:</b>	Mixing	Product supplied ready for use
	Method	Spatula or putty knife
	Cleaning:	Clean equipment immediately after use with water.
	Drying time:	At 23°C and 65% Relative Humidity
		Sand: 30 min
<b>Storage and Packaging:</b>	Store away from direct sun, heat and severe cold. Packaging: 10 kg, 500 g	
<b>Surface Preparation:</b>	<ul style="list-style-type: none"> <li>• Surface must be dry, clean and free of contaminants</li> <li>• May be overcoated with Nitrocellulose (<b>SS</b> or <b>WL/ANL</b>) or <b>PLASCOLAC REACTION LACQUER</b> system (<b>EZN</b>)</li> </ul>	
<b>Application</b>	<ul style="list-style-type: none"> <li>• Apply by spatula into shallow imperfections.</li> </ul>	
<b>Safety Precautions</b>	<ul style="list-style-type: none"> <li>• Keep out of reach of children.</li> <li>• Ensure good ventilation during application and drying.</li> <li>• In case of skin contact, wash with soap and water or a recognised skin cleaner.</li> <li>• Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist.</li> <li>• Harmful if swallowed. Do not induce vomiting. Seek medical attention.</li> <li>• Refer to Material Safety Data Sheet for complete information.</li> </ul>	

#### **DISCLAIMER:**

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

**NB:** Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

**NB: TO ORDER:** Quote product name, product code number, packaging and colour.

#### **KANSAI PLASCON (PTY) LIMITED**

##### **CAPE TOWN:**

P O Box 42  
Eppindust 7475  
Tel: (021) 505.2400  
Fax: (021) 534-3791

##### **DURBAN:**

Private Bag X16  
Mobeni 4060  
Tel: (031) 451-3200  
Fax: (031) 451-3411

##### **GAUTENG:**

Private Bag X4010  
Kenmare 1745  
Tel: (011) 951-4500  
Fax: (011) 955-2841

##### **PORT ELIZABETH:**

P O Box 1594  
Port Elizabeth 6000  
Tel: (041) 401-1400  
Fax: (041) 453-4606