

## CATALYST FOR PLASCOTHANE UPF 4-1 SERIES

**PRODUCT CODE: KAT 400**

### TECHNICAL DATA SHEET

<b>Product Description</b>	Aliphatic polyisocyanate catalyst for 2 pack polyurethane systems.	
<b>Intended Uses</b>	Used to catalyse the <b>PLASCOTHANE WOODFINISH POLYURETHANES (UPF 4-1 Series)</b> .	
<b>Product Information</b>	Appearance	Colourless liquid
	Type	Hydrocarbon solvents
	SG at 23°C:	1.04 kg/L (typical)
<b>Application Details</b>	Mixing	Mixing Ratio: 4 parts UPF to 1-part KAT 400 by volume
<b>Storage and Packaging:</b>	Should be stored indoors in the original, unopened and undamaged container, in a dry place at a temperature not exceeding 30 °C. Exposure to direct sunlight should be avoided.	
<b>Safety Precautions</b>	<ul style="list-style-type: none"> <li>• Flammable - Keep away from source of ignition, flames, sparks and heat.</li> <li>• Use only in well ventilated environments.</li> <li>• Do not smoke during use.</li> <li>• Keep out of reach of children.</li> <li>• Dangerous if swallowed. Seek medical attention immediately.</li> <li>• Do not induce vomiting.</li> <li>• Avoid contact with skin and eyes.</li> <li>• Do not dispose of into natural water-ways or drainage system.</li> <li>• Refer to Safety Data Sheet for complete information.</li> </ul>	

#### **DISCLAIMER:**

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

**NB:** Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

**NB: TO ORDER:** Quote product name, product code number, packaging and colour.

#### **KANSAI PLASCON (PTY) LTD**

10 Frederick Cooper Drive,  
Factoria, Krugersdorp  
South Africa  
1739.  
Tel: +27 11 951 4500  
Fax: +27 800 110 932

**PLASCON ADVISORY SERVICE:** 0860 20 40 60

**EMAIL:** advice@kansaiplascon.co.za