

UV ACRYLIC SEALER

PRODUCT CODE: MEV 3009

TECHNICAL DATA SHEET

Product Description	This product is an UV curable acrylic sealer.	
Intended Uses	<ul style="list-style-type: none"> This product is designed specifically for wooden substrates, used for interior wooden furniture and panelling. For use directly onto flat medium density fibreboard, solid timber, veneers and suitable paper foils. 	
Features & Benefits	<ul style="list-style-type: none"> Good sealing properties. Good sanding properties. 	
Product Information	Colour Viscosity at 23°C Specific Gravity Flash Point	Clear (MEV 3009) 100 - 120" Ford Cup No. 4 1,25 Below 12 °C
Application Details	Mixing Method Thinning Cleaning Drying times	Ready to use. Stir the product well. Roller-coater Use BUTYL ACETATE Clean equipment with BUTYL ACETATE . Roller-coating machine can be drained and covered with black plastic if left overnight. UV Curing: 6.5m / min per lamp Sand: After curing Overcoat: After curing Stack / Rack: After curing Wrap: After curing
Storage and Packaging	Store away from direct sun, heat and severe cold. Keep out of direct light, as the product is sensitive to light. Packaging: 25 L	
Surface preparation	<ul style="list-style-type: none"> Suitably calibrated flat wooden surfaces must be dry and free of contaminants, sanded to a smooth finish with a suitable grade of sandpaper. Remove all sanding dust prior to application. This product can be overcoated with most interior furniture topcoats 	
Application	<ul style="list-style-type: none"> Apply @ 8 - 20 g/m² per coat depending on application equipment, with sanding or pre-gel between coats. 	
Caution	<ul style="list-style-type: none"> This material is flammable and must not be exposed to naked flame. Do not inhale vapours. Use in correctly ventilated areas only. 	
Safety Precautions	<ul style="list-style-type: none"> Always keep paint out of reach of children. Ensure good ventilation during application and drying. If accidental contact with skin should occur, wash immediately with soap and water or a recognised skin cleaner. Take care to avoid contact with the eyes. In case of contact, immediately rinse the eyes with plenty of water and seek medical attention. Harmful if swallowed. Seek medical attention and do not induce vomiting. Refer to Safety Data Sheet for complete information 	



UV ACRYLIC SEALER

PRODUCT CODE: MEV 3009

DISCLAIMER:

The recommendations contained herein are given in all good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

NB: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging and colour.

KANSAI PLASCON (PTY) LTD

10 Frederick Cooper Drive,
Factoria, Krugersdorp
South Africa
1739.
Tel: +27 11 951 4500
Fax: +27 800 110 932

PLASCON ADVISORY SERVICE: 0860 20 40 60

EMAIL: advice@kansaiplascon.co.za

