

PENETRATING FURNITURE OIL

PRODUCT CODE: PFO 1

TECHNICAL DATA SHEET

Product Description	A penetrating clear furniture oil for the preservation of softwoods & hardwoods	
Intended Uses	Sealing of timber with a penetrating finish for joinery applications. Also to impart an oiled type finish to timber. Recommended for exterior use in conjunction with Water Based Wax (WBW1) as a topcoat.	
Features & Benefits	<ul style="list-style-type: none"> • Good penetrating & sealing properties. • Can be tinted with IAC tinters 	
Product Information	Colour Viscosity at 23 °C Specific Gravity at 23 °C Flash Point	Clear 11" Ford Cup No. 4 0.81 35 °C
Application Details	Mixing Method Thinning Cleaning Drying time	Stir contents of the container thoroughly with a flat paddle till homogeneous. May be applied by ragging, dipping or spraying. NOT RECOMMENDED for circulating dipping taps Ready for use Clean equipment immediately after use with LACQUER THINNERS (ILS 1) or mineral turpentine. Dry to Handle: 1 Hour Overcoat: 24 Hours. Depending on the porosity.
Storage & Packaging	Store away from direct sun, heat and severe cold. Packaging: 25 ℓ and 200 ℓ	
Surface preparation	<ul style="list-style-type: none"> • Sand in the direction of the grain to a smooth finish with 150 grit sandpaper and remove dust. • If previously coated with oil based preservative, rub down the surface with "scotch brite" or steel wool. 	
Application	<ul style="list-style-type: none"> • Can be applied by ragging, dipping or spraying. • A small quantity of IAC toners may be added. 	
Caution	<ul style="list-style-type: none"> • Note: All rags used to apply oil must be washed in solvent and allowed to dry as spontaneous combustion of these rags soaked in PFO1 can occur. • This material is flammable and must not be exposed to naked flame. • Do not inhale vapours. • Use in correctly ventilated areas only 	
Safety Precautions	<ul style="list-style-type: none"> • Always keep paint out of reach of children. • Ensure good ventilation during application and drying. • If accidental contact with skin should occur, wash immediately with soap and water or a recognised skin cleaner. • Take care to avoid contact with the eyes. In case of contact, immediately rinse the eyes with plenty of water and seek medical attention. • Harmful if swallowed. Seek medical attention and do not induce vomiting. • Refer to Material Safety Data Sheet for complete information 	



PENETRATING FURNITURE OIL

PRODUCT CODE: PFO 1

DISCLAIMER:

The recommendations contained herein are given in all good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

NB: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging and colour.

KANSAI PLASCON (PTY) LIMITED

CAPE TOWN:

P O Box 42
Eppindust 7475
Tel: (021) 505-2400
Fax: (021) 534-3791

DURBAN:

Private Bag X16
Mobeni 4060
Tel: (031) 451-3200
Fax: (031) 451-3411

GAUTENG:

P.O. Box 4010
Luipaardsvlei 1743
Tel: (011) 951-4500
Fax: (011) 955-2841

PORT ELIZABETH:

P O Box 1594
Port Elizabeth 6000
Tel: (041) 401-1400
Fax: (041) 453-4606

