

## CELLULOSE MATTING PASTE

**PRODUCT CODE: SS 12**

### TECHNICAL DATA SHEET

<b>Product Description</b>	A matting paste for use in Nitrocellulose (WL) lacquers.	
<b>Intended Uses</b>	Gloss reduction of NC lacquers.	
<b>Product Information</b>	Colour:	Beige to light brown
	Specific Gravity:	1.02
<b>Application Details</b>	Matting a product	<ol style="list-style-type: none"> <li>1. Gloss levels can be affected by the method of incorporation of SS 12.</li> <li>2. The ideal incorporation method is to mix for 5 min using a shaker.</li> <li>3. Caution: As the addition of flattening paste may result in an over-filled product, it is recommended that the product is decanted into a mixing vessel, matted down and then the original tin/s refilled to the correct level.</li> <li>4. Ensure that the entire "customer order batch" is mixed uniformly before filling.</li> </ol>
	Thinner Cleaning	<p>Ready for use. Do not thin.</p> <p><b>UNIVERSAL REDUCER (PUR 1), ENAMEL THINNER (TH 77), TULUOL REDUCER (HVL 1), FAST DRYING SOLVENT (PYY 1) or LACQUER THINNER (ILS 1).</b></p>
<b>Storage and Packaging:</b>	<p>Store away from direct sun, heat and severe cold.</p> <p>Packaging: 1 kg</p>	
<b>Safety Precautions</b>	<ul style="list-style-type: none"> <li>• Always keep paint out of reach of children.</li> <li>• Ensure good ventilation during application and drying.</li> <li>• If accidental contact with skin should occur, wash immediately with soap and water or a recognised skin cleaner.</li> <li>• Take care to avoid contact with the eyes. In case of contact, immediately rinse the eyes with plenty of water and seek medical attention.</li> <li>• Harmful if swallowed. Seek medical attention and do not induce vomiting.</li> <li>• Do not smoke while painting.</li> <li>• Flammable. Store in a cool dry place away from heat and sparks.</li> <li>• Refer to Safety Data Sheet for complete information.</li> </ul>	

#### **DISCLAIMER:**

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

**NB:** Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

**NB: TO ORDER:** Quote product name, product code number, packaging and colour.

#### **KANSAI PLASCON (PTY) LIMITED**

10 Frederick Cooper Drive,  
Factoria, Krugersdorp,  
1739.  
Tel: 011 951 4500  
Fax: 0800 110 932

**PLASCON ADVISORY SERVICE:** 0860 20 40 60

**EMAIL:** advice@kansaiplascon.co.za

