

PLASCOTHANE WOODFINISH POLYURETHANE CLEAR

PRODUCT CODE: UPF 2007

TECHNICAL DATA SHEET

Product Description	UPF 2007 is a dual pack polyurethane acrylic finish.													
Intended Uses	<ul style="list-style-type: none"> For interior and exterior furniture, office furniture and kitchen and bar counter tops 													
Features & Benefits	<ul style="list-style-type: none"> An attractive smooth gloss finish that is easy to keep clean Good durability Good chemical resistance with good colour retention Quick drying - touch dry in 30 min Non-yellowing Good mar resistance 													
Product Information	Appearance	Full gloss												
	Colour	Clear (UPF 2007)												
	Generic type	Acrylic												
	Solvents type	Aromatic hydrocarbons, acetates and esters												
	Solids	Approx. 37 % by volume												
	S G at 23°C	Approx. 0.98 kg/L												
	Recommended DFT	25 - 40 µm per coat												
	Recommended WFT	68 – 108 µm												
	Spread rate	100 – 120g/m ² per coat												
	Viscosity at 23 °C	115 – 120 sec												
	Flash Point	23 °C												
	Pot-life	6 h												
	VOC	531 g/L												
Application Details	Mixing	Stir thoroughly with a flat paddle until homogeneous. Mix in ratio supplied.												
	Method	4 parts BASE to 1 Part CATALYST (KAT 400) by volume Conventional spray, air assisted airless or a pressure pot system. The recommended air pressures are as follows: - Air Assisted Airless: Pump pressure 1.5 - 2 bar Atomising air pressure 1 - 1.5 bar Pressure Pot: Pressure pot pressure 1 - 1.5 bar Atomising air pressure 1.5 bar Use only stainless-steel spray application equipment. Nozzle sizes 1.4 – 1.8mm.												
	Thinning	Use PUR 1 (PLASCON UNIVERSAL REDUCER) for thinning to a spraying viscosity of approx. 18 seconds at 23 °C in Ford Cup No. 4.												
	Cleaning	PLASCON UNIVERSAL REDUCER (PUR 1) or LACQUER THINNER (ILS 1)												
	Drying time	Touch dry: 30 min. @ 23 °C (50% Relative Humidity) Dry to handle: 4 h @ 23 °C Full cure: 7 days @ 23 °C												
	Application Environment	<table border="1"> <thead> <tr> <th>Surface Temperature</th> <th>Ambient Temperature</th> <th>Relative Humidity</th> </tr> </thead> <tbody> <tr> <td>Min: 10 °C</td> <td>Min: 10 °C</td> <td>Min: 10 %</td> </tr> <tr> <td colspan="3">Or 3 °C min above dew point</td> </tr> <tr> <td>Max: 40 °C</td> <td>Max: 40 °C</td> <td>Max: 85 %</td> </tr> </tbody> </table>	Surface Temperature	Ambient Temperature	Relative Humidity	Min: 10 °C	Min: 10 °C	Min: 10 %	Or 3 °C min above dew point			Max: 40 °C	Max: 40 °C	Max: 85 %
Surface Temperature	Ambient Temperature	Relative Humidity												
Min: 10 °C	Min: 10 °C	Min: 10 %												
Or 3 °C min above dew point														
Max: 40 °C	Max: 40 °C	Max: 85 %												
Storage & Packaging	Store away from direct sun, heat and severe cold. Packaging: Base 4 L and Catalyst (KAT 400) 1 L													

PLASCOTHANE WOODFINISH POLYURETHANE CLEAR

PRODUCT CODE: UPF 2007

Surface Preparation	<ul style="list-style-type: none"> • Surface must be dry, clean and free of contaminants • Sand to a smooth surface, free of loose fibres • Sand substrate with 150 – 180 grit sand paper to a smooth finish • Remove all dust prior to the application of the clear coating.
Application	<ul style="list-style-type: none"> • If application equipment was used previously for water-based product, ensure all the equipment is washed with water then alcohol followed by solvent LACQUER THINNERS (ILS 1). • Apply at a rate of 100 – 120g/m² per coat. Do not apply more than 180g/m². • Allow the coating to dry as specified. • Sand with 320 – 400 grit sand paper. • Remove all sanding dust prior to further application.
Caution	<ul style="list-style-type: none"> • Do not apply directly to acrylic lacquers and synthetic alkyd enamels
Safety Precautions	<ul style="list-style-type: none"> • Keep out of reach of children. • Ensure good ventilation during application and drying. • Do not pour paint down the drain. • In case of skin contact, wash with soap and water or a recognised skin cleaner. • Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist. • Do not smoke while painting. • Harmful if swallowed. Do not induce vomiting. Seek medical attention. • Refer to Safety Data Sheet for complete information.

DISCLAIMER:

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

NB: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging and colour.

KANSAI PLASCON (PTY) LIMITED

10 Frederick Cooper Drive,

Factoria, Krugersdorp

South Africa

1739.

Tel: +27 11 951 4500

Fax: +27 800 110 932

PLASCON ADVISORY SERVICE: 0860 20 40 60

EMAIL: advice@kansaiplascon.co.za