

## WATER BASED WAX

PRODUCT CODE: WBW 1

### TECHNICAL DATA SHEET

<b>Product Description</b>	A water based wax finish.	
<b>Intended Uses</b>	A clear water based wax to protect wood surfaces.	
<b>Features&amp; Benefits</b>	<ul style="list-style-type: none"> <li>• Easy to apply</li> <li>• Imparts a silky/wax feel to the surface</li> <li>• Water-repellent properties.</li> </ul>	
<b>Product Information</b>	Appearance	Low sheen
	Colour	Amber Liquid
	Specific Gravity at 23°C	0.99 kg/ℓ
	pH	8.3
	Flash Point:	Non Flammable
<b>Application Details</b>	Mixing	Stir contents of container thoroughly with a flat paddle until homogeneous.
	Method	Rag, damp cloth, sponge, dip or spray.
	Thinning	Up to 50:50 with water
	Cleaning:	Clean equipment immediately after use with water.
	Drying time:	At 23 °C & 65% Relative Humidity
		Dust free: 20 minutes
		Handling: 30 minutes
		Recoating: 30 minutes (Usually not required)
<b>Storage and Packaging</b>	Store away from direct sun, heat and severe cold.	
	Packaging: 25 ℓ; 200 ℓ	
<b>Surface Preparation</b>	<ul style="list-style-type: none"> <li>• Sand in the direction of the grain to a smooth finish with 150 grit sandpaper and remove dust.</li> <li>• If previously coated with oil based preservative, rub down the surface with scotch-brite scouring pads or steel wool.</li> </ul>	
<b>Application</b>	<ul style="list-style-type: none"> <li>• Water can be added when ragging or dipping in order to improve workability and prevent excess wax build up.</li> <li>• Thin with minimum 10% &amp; maximum 50% water.</li> <li>• <b>WATER BASED WAX (WBW 1)</b> must not be applied too heavily, to increase the sheen of the finished product. allow to dry and lightly abrade with a scotch-brite scouring pad.</li> <li>• Recommended base/topcoat: <b>PINE FURNITURE OIL (PFO 1)</b> is the recommended sealer.</li> </ul>	
<b>Caution</b>	<ul style="list-style-type: none"> <li>• Not suitable for over coating lacquered surfaces. Apply over oils and stains where the wood grain accepts wax penetration.</li> <li>• Avoid contact with strong acids &amp; alkalis</li> </ul>	
<b>Safety Precautions</b>	<ul style="list-style-type: none"> <li>• Keep out of reach of children.</li> <li>• Ensure good ventilation during application and drying.</li> <li>• In case of skin contact, wash with soap and water or a recognised skin cleaner.</li> <li>• Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist.</li> <li>• Harmful if swallowed. Do not induce vomiting. Seek medical attention.</li> <li>• Refer to Material Safety Data Sheet for complete information</li> </ul>	

## **WATER BASED WAX**

**PRODUCT CODE: WBW 1**

---

**DISCLAIMER:**

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

**N.B.** Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

**NB: TO ORDER: Quote product name, product code number, packaging and colour.**

**KANSAI PLASCON (PTY) LIMITED**

**CAPE TOWN:**

P O Box 42  
Eppindust 7475  
Tel: (021) 505-2400  
Fax: (021) 534-3791

**DURBAN:**

Private Bag X16  
Mobeni 4060  
Tel: (031) 451-3200  
Fax: (031) 451-3411

**GAUTENG:**

P.O. Box 4010  
Luipaardsvlei 1743  
Tel: (011) 951-4500  
Fax: (011) 955-2841

**PORT ELIZABETH:**

P O Box 1594  
Port Elizabeth 6000  
Tel: (041) 401-1400  
Fax: (041) 453-4606