

## WATERBASED PENETRATING STAIN

PRODUCT CODE: WPS Series

### TECHNICAL DATA SHEET

|                                |   |  |
|--------------------------------|---|--|
| <b>Product Description</b>     | <b>WATERBASED PENETRATING STAIN</b> contains soluble dyes in a balanced blend of solvent and water.   |  |
| <b>Intended Uses</b>           | This range is suitable for use on all interior wood and can be over coated with <b>FFW series</b> or <b>WFC series</b> .  |  |
| <b>Features &amp; Benefits</b> | <ul style="list-style-type: none"> <li>• Excellent open time.</li> <li>• Excellent penetration of timber when used as a base stain</li> <li>• Good drying characteristics</li> <li>• Excellent clarity and timber definition</li> <li>• Can be used as a tint in <b>FFW</b> system</li> </ul>   |  |
| <b>Product Information</b>     | Colour  | Black (WPS 1); Red (WPS 2); Yellow (WPS 4);                                    |
|                                | Viscosity at 23 °C  | 10 - 12" Ford Cup No. 4  |
|                                | SG at 23 °C   | 1  |
|                                | Flash Point   | N/A  |
| <b>Application Details</b>     | Mixing  | Stir contents of the container thoroughly with a flat paddle until homogeneous |
|                                | Method  | May be applied by rag, brush, dipping or spray                                 |
|                                | Thinning  | Water  |
|                                | Cleaning  | Water  |
|                                | Drying time   | At 23 °C and 65% Relative humidity   |
|                                |   | Dry to Handle: 15 Min  |
|                                |   | Overcoat: 30 Min   |
| <b>Storage &amp; Packaging</b> | Store away from direct sun, heat and severe cold.<br>Packaging: 5 L plastic container.  |  |
| <b>Surface preparation</b>     | <ul style="list-style-type: none"> <li>• Wood surfaces must be dry, clean and free of dust/contaminants</li> <li>• Sand to a smooth finish with a suitable grade of sand paper</li> <li>• Remove all sanding dust prior to staining</li> </ul>  |  |
| <b>Application</b>             | <ul style="list-style-type: none"> <li>• When applying by rag or brush saturate the timber and wipe off the excess</li> <li>• Build up colour with mist coats to achieve desired colour</li> </ul>  |  |
| <b>Safety Precautions</b>      | <ul style="list-style-type: none"> <li>• Always keep paint out of reach of children.</li> <li>• Ensure good ventilation during application and drying.</li> <li>• If accidental contact with skin should occur, wash immediately with soap and water or a recognised skin cleaner.</li> <li>• Take care to avoid contact with the eyes. In case of contact, immediately rinse the eyes with plenty of water and seek medical attention.</li> <li>• Harmful if swallowed. Seek medical attention and do not induce vomiting.</li> <li>• Refer to Safety Data Sheet for complete information</li> </ul> |  |

## WATERBASED PENETRATING STAINS

PRODUCT CODE: WPS Series

---

**DISCLAIMER:**

The recommendations contained herein are given in all good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

**NB:** Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

**NB: TO ORDER:** Quote product name, product code number, packaging and colour.

**KANSAI PLASCON (PTY) LTD**

10 Frederick Cooper Drive,  
Factoria, Krugersdorp  
South Africa  
1739.

Tel: +27 11 951 4500

Fax: +27 800 110 932

**PLASCON ADVISORY SERVICE:** 0860 20 40 60

**EMAIL:** [advice@kansaiplascon.co.za](mailto:advice@kansaiplascon.co.za)