

AQUASOLV DEGREASER

PRODUCT CODE: GR 1

TECHNICAL DATA SHEET

Product Description	A water emulsifiable degreaser solution for heavy duty cleaning.	
Intended Uses	<ul style="list-style-type: none"> • AQUASOLV DEGREASER is a water rinse-able degreaser for the effective and efficient removal of oil, grease, wax and release agents used in off shutter or pre-cast concrete from surfaces to be painted. • General degreaser and cleaner for steel surfaces in the surface preparation process. • In the motor trade for degreasing of cold engines, factory machinery and agricultural equipment before spray coating. • For industrial and household use to clean oily and greasy enamel painted walls, garage floors and to remove floor polish prior to varnishing or painting. 	
Features & Benefits	<ul style="list-style-type: none"> • Excellent general surface cleaner • For Industrial and household use 	
Product Information	Appearance	Low viscosity liquid
	Colour	Clear
	Generic type	Hydrocarbon solvents and detergents
	Flash point	> 50 °C
	Practical Spreading rate	Approx.10 m ² /L for normal cleaning purposes. The actual spreading rate depends on the condition and porosity of the surface to be cleaned.
Application Details	Mixing Method	Mix well by shaking container before use. Cloth, bristle brush, broom
	Thinning	For heavy duty cleaning use as supplied. For removal of light greases and oils (e.g. enamel painted walls) dilute up to 1 part AQUASOLV DEGREASER to 2 parts water by volume. NOTE: Product turns milky when mixed with water.
	Cleaning	Rinse thoroughly with water to achieve a water break-free surface.
Storage & Packaging	Store away from direct sun, heat and severe cold. Packaging: 5 L and 25 L	
Application	<ul style="list-style-type: none"> • Swab the AQUASOLV DEGREASER onto the soiled surface using a cloth, bristle brush/broom and work the solution well into the surface. Scotchbrite scouring pads are ideal for cleaning off-shutter concrete surfaces, plastered walls or non-ferrous metals. • Allow approximately 15 minutes for the active solvents to penetrate and soften the deposits and then thoroughly flush off with fresh water while scrubbing with a hard bristle brush/broom until the wash water is completely clear and free from foam. • Heavy deposits and deeply penetrated oil stains may require repeated applications of AQUASOLV DEGREASER. • N.B. A repeat application is necessary when the flushing with water does not give a complete water break-free surface. 	
Cautions	<ul style="list-style-type: none"> • Do not use on plastic and other surfaces that may be attacked by AQUASOLV DEGREASER. If unsure test it in an inconspicuous spot. • DO NOT USE ON TAR SURFACES • Flammable - Do not apply to hot surfaces. • After use always ensure that all traces of AQUASOLV DEGREASER are rinsed off. 	

AQUASOLV DEGREASER

PRODUCT CODE: GR 1

Safety Precautions

- Keep out of reach of children.
 - Ensure good ventilation during application and drying.
 - If accidental contact with skin should occur, wash immediately with soap and water or a recognised skin cleaner.
 - Take care to avoid contact with the eyes. In case of contact, immediately rinse the eyes with plenty of water and seek medical attention.
 - Harmful if swallowed. Seek medical attention and do not induce vomiting.
 - Do not smoke while using the product.
 - Flammable. Store in a cool dry place away from heat and sparks.
 - Refer to Safety Data Sheet for complete information.
-

DISCLAIMER:

The recommendations contained herein are given in all good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

N.B. Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

N.B. TO ORDER: Quote product name, product code number, packaging and colour.

KANSAI PLASCON (PTY) LIMITED

10 Frederick Cooper Drive,
Factoria, Krugersdorp
South Africa
1739.

Tel: +27 11 951 4500

Fax: +27 800 110 932

PLASCON ADVISORY SERVICE: 0860 20 40 60

EMAIL: advice@kansaiplascon.co.za