

WATERBASED GLAZE COAT CLEAR

PRODUCT CODE: REF 1124 & 1125

TECHNICAL DATA SHEET

Product Description	A clear non-yellowing acrylic emulsion glaze coat available in gloss and matt finishes.													
Intended Uses	<ul style="list-style-type: none"> To provide a protective coat over waterbased paint techniques. To provide a uniform sheen and appearance to coated walls. To seal walls coated with waterbased emulsion texture coatings. To render wall surfaces coated with matt emulsion paints and walls covered with non-washable wallpapers washable. 													
Features & Benefits	<ul style="list-style-type: none"> Non-yellowing. Improves surface washability. Improves durability and dirt resistance. Excellent adhesion. 													
Product Information	Appearance Solids S G Recommended DFT Theoretical spreading rate VOC	Gloss: (REF 1124), Matt: (REF 1125) Approx. 32 % by mass; 27 % by volume 1,03 (typical) Min: 20 µm Max: 30 Approx. 10.8 m ² /L at 25 µm. This serves as a guide only 0 g/L (REF 1124) 44 g/L (REF 1125)												
Application Details	Mixing Method Thinning Cleaning Drying time Application Environment	Stir thoroughly with a flat paddle until homogeneous. Brush, roller or airless spray Water Water Touch dry: 1 h @ 23 °C Over coating: 2 h @ 23 °C <table border="1"> <thead> <tr> <th>Surface Temperature</th><th>Ambient Temperature</th><th>Relative Humidity</th></tr> </thead> <tbody> <tr> <td>Min.: 10 °C</td><td>Min.: 10 °C</td><td>Min.: 10%</td></tr> <tr> <td colspan="3">or 2 °C min. above dew point</td></tr> <tr> <td>Max.: 40 °C</td><td>Max.: 40 °C</td><td>Max.: 85%</td></tr> </tbody> </table>	Surface Temperature	Ambient Temperature	Relative Humidity	Min.: 10 °C	Min.: 10 °C	Min.: 10%	or 2 °C min. above dew point			Max.: 40 °C	Max.: 40 °C	Max.: 85%
Surface Temperature	Ambient Temperature	Relative Humidity												
Min.: 10 °C	Min.: 10 °C	Min.: 10%												
or 2 °C min. above dew point														
Max.: 40 °C	Max.: 40 °C	Max.: 85%												
Storage and Packaging	Store away from direct sun, heat and severe cold. Packaging: 1L and 5L													
Surface Preparation	<ul style="list-style-type: none"> Ensure that surfaces are dry, sound and free from dust, dirt, grease and oil before painting. Clean down all surfaces with POLYCELL SUGAR SOAP solution to remove all traces of dirt and oil. Rinse thoroughly with clean water and allow to dry. 													
Application	<ul style="list-style-type: none"> Apply as supplied by brush, roller or airless spray. One coat is sufficient in most cases. 													
Cautions	<ul style="list-style-type: none"> Not recommended for floors or furniture/ kitchen cupboards. REF 1124 GLOSS is suitable for interior and exterior applications, but REF 1125 MATT only for interior use. REF 1124 & 1125 is not recommended for use over solvent based alkyd paints. DO NOT thin with solvents. DO NOT apply over alkyd enamel based paints. Avoid application during inclement weather or if temperature is below 10 °C. 													



WATERBASED GLAZE COAT CLEAR

PRODUCT CODE: REF 1124 & 1125

Safety Precautions

- Keep out of reach of children.
 - Ensure good ventilation during application and drying.
 - In case of skin contact, wash with soap and water or a recognised skin cleaner.
 - Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist.
 - Harmful if swallowed. Do not induce vomiting. Seek medical attention.
 - Refer to Safety Data Sheet for complete information.
-

DISCLAIMER:

The recommendations contained herein are given in all good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

NB: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging and colour.

KANSAI PLASCON (PTY) LIMITED

10 Frederick Cooper Drive,
Factoria, Krugersdorp
South Africa
1739.

Tel: +27 11 951 4500
Fax: +27 800 110 932

PLASCON ADVISORY SERVICE: 0860 20 40 60

EMAIL: advice@kansaiplascon.co.za

