

AEROLAK METALLIC SPRAY PAINT

PRODUCT CODE: 911013 - 911020

TECHNICAL DATA SHEET

Product Description	A high quality quick drying aerosol spray paint with a high gloss metallic finish.													
Intended Uses	<ul style="list-style-type: none"> Used for numerous domestic, industrial and touch-up purposes. Suitable for both interior and exterior application. 													
Features & Benefits	<ul style="list-style-type: none"> AEROLAK METALLIC is formulated with high quality resins and produces a durable, non-yellowing high gloss coating. The paint film has good flexibility and is able to withstand light impact. 													
Product Information	Appearance Colours Mass solids S G Generic type	High gloss with sparkle A range of colours 16 % (typical) 0,80 kg/L (typical) Nitrocellulose/acrylic resin												
Application Details	Mixing Method Cleaning Application Environment Drying time	Shake can vigorously prior to use until the built-in agitator moves freely. Shake at intervals during use to ensure product remains homogeneous. Aerosol spray POLYCELL BRUSH CLEANER <table border="1"> <tr> <th>Surface Temperature</th><th>Ambient Temperature</th><th>Relative Humidity</th></tr> <tr> <td>Min: 10 °C</td><td>Min: 10 °C</td><td>Min: 10 %</td></tr> <tr> <td colspan="3">or 3 °C min. above dew point</td></tr> <tr> <td>Max: 40 °C</td><td>Max: 40 °C</td><td>Max: 85 %</td></tr> </table> Touch dry Overcoating Dry to handle	Surface Temperature	Ambient Temperature	Relative Humidity	Min: 10 °C	Min: 10 °C	Min: 10 %	or 3 °C min. above dew point			Max: 40 °C	Max: 40 °C	Max: 85 %
Surface Temperature	Ambient Temperature	Relative Humidity												
Min: 10 °C	Min: 10 °C	Min: 10 %												
or 3 °C min. above dew point														
Max: 40 °C	Max: 40 °C	Max: 85 %												
Storage and Packaging	Store away from direct sun and heat as material is highly flammable. Store away from severe cold. Packaging: 300 ml Aerosol can.													
Surface Preparation	<ul style="list-style-type: none"> All surfaces must be clean and dry and free from rust, oil or old paint. Remove oil and dirt with POLYCELL BRUSH CLEANER and rinse thoroughly with fresh water. Metal: Completely remove any rust back to bright metal with an abrasive e.g. wire brushing, sanding, emery cloth, etc. Strip old paint by most suitable means. Prime unpainted surfaces with AEROLAK GREY PRIMER (911066). 													
Application	<ul style="list-style-type: none"> After shaking, hold can upright ± 25 - 30 cm from the surface to be coated and spray evenly moving across the surface with a side to side motion releasing the nozzle to discontinue spraying after each pass. Apply light successive overlapping coats to avoid running or sagging of material. Allow to dry between coats. Apply up to two coats as required to achieve complete obliteration. Although it bonds well to bare metal, glass, masonry and wood, unpainted surfaces should be primed with AEROLAK GREY PRIMER (911066). After use invert can and depress nozzle until it ceases to spray. This process will clear the valve and nozzle and avoid clogging during storage. 													

AEROLAK METALLIC SPRAY PAINT

PRODUCT CODE: 911013 - 911020

TECHNICAL DATA SHEET

Cautions	<ul style="list-style-type: none"> • Not suitable for polystyrene and plastic. • Do Not spray CLEAR Aerolak over AEROLAK METALLIC SPRAY PAINT as it destroys the leafing properties of the metallic paint • Poor spray pattern: This occurs as a result of the product being stored at temperatures less than 10 °C. To re-constitute, warm can gently by immersing in warm (NOT boiling) water for 2 - 3 minutes. Product is now ready for use. • Nozzle blocked: Remove nozzle and replace after cleaning with PLASCON LACQUER THINNER (ILS 1). • Poor coverage: Separation of paint has occurred within the can. Shake the can vigorously for ½ - 1 minute prior to spraying.
Safety Precautions	<ul style="list-style-type: none"> • Keep out of reach of children. • Highly flammable - Keep away from open flames, sparks and heat. • Do not smoke during use. • Ensure good ventilation during application and drying. • Do not puncture or incinerate container as content is under pressure. • Refer to Safety Data Sheet for complete information.

DISCLAIMER:

The recommendations contained herein are given in all good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

N.B. Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging and colour.

KANSAI PLASCON (PTY) LIMITED

10 Frederick Cooper Drive,
Factoria, Krugersdorp
South Africa
1739.
Tel: +27 11 951 4500
Fax: +27 800 110 932

PLASCON ADVISORY SERVICE: 0860 20 40 60

EMAIL: advice@kansaiplascon.co.za