

TRUE COLOUR FRESH WHITE - APPLE FRAGRANCE

PRODUCT CODE: ATC 1

TECHNICAL DATA SHEET

Product Description	A water based acrylic PVA.													
Intended Uses	<ul style="list-style-type: none"> For use on both exterior and interior surfaces. Used on suitably prepared and primed new plaster, concrete, porous brickwork and various types of building boards. 													
Features & Benefits	<ul style="list-style-type: none"> High hiding Smooth white finish Easy application by brush and roller Apple fragrance allows to stay comfortably soon after painting Zero VOC 													
Product Information	Appearance	Matt												
	Colour	White												
	Generic type	Modified acrylic emulsion												
	Solids	33 % by volume												
	Recommended DFT	25 – 35 µm per coat												
	Recommended WFT	76 – 106 µm per coat												
	Theoretical spreading rate	11 m ² /L per coat @ 30 µm DFT. This serves as a guide only.												
	Practical spreading rate	The practical spreading rate will vary depending on the profile of the substrate, as well as the application technique and tools used.												
	VOC	0 g/L												
Application Details	Mixing	Stir thoroughly with a flat paddle until homogeneous.												
	Method	Brush, roller or airless spray.												
	Thinning	Not recommended												
	Cleaning	Water												
	Drying time	Touch dry: 30 mins @ 23 °C Over coating: 1 h @ 23 °C												
	Application Environment	<table border="1"> <tr> <th>Surface Temperature</th><th>Ambient Temperature</th><th>Relative Humidity</th></tr> <tr> <td>Min: 10 °C</td><td>Min: 10 °C</td><td>Min: 10 %</td></tr> <tr> <td colspan="3">or 3 °C min. above dew point</td></tr> <tr> <td>Max: 40 °C</td><td>Max: 40 °C</td><td>Max: 85 %</td></tr> </table>	Surface Temperature	Ambient Temperature	Relative Humidity	Min: 10 °C	Min: 10 °C	Min: 10 %	or 3 °C min. above dew point			Max: 40 °C	Max: 40 °C	Max: 85 %
Surface Temperature	Ambient Temperature	Relative Humidity												
Min: 10 °C	Min: 10 °C	Min: 10 %												
or 3 °C min. above dew point														
Max: 40 °C	Max: 40 °C	Max: 85 %												
Storage & Packaging	Store away from direct sun and severe cold. Packaging: 5 L and 20 L													

TRUE COLOUR FRESH WHITE - APPLE FRAGRANCE

PRODUCT CODE: ATC 1

TECHNICAL DATA SHEET

Surface	Ensure that surfaces are dry, sound, and free from dust, dirt, grease and oil before painting.
Preparation	<ol style="list-style-type: none"> 1. NEW WORK 1.1 <u>Cement plaster, concrete:</u> Remove any loose particles and laitance by most suitable means. Prime with TRUE COLOUR 3 IN 1 PRIMER SEALER UNDERCOAT (PSU 1). N.B. Soft, under bound, friable and highly porous surfaces must be restored to a sound condition with PLASCON BONDING LIQUID (CVI 14) 1.2 <u>Gypsum plaster (e.g. Rhinolite, Cretestone), gypsum board:</u> Apply one coat of TRUE COLOUR 3 IN 1 PRIMER SEALER UNDERCOAT (PSU 1). If a gypsum plaster has been used as the joint skimming filler on gypsum board or dry wall partitioning, then seal these areas with TRUE COLOUR 3 IN 1 PRIMER SEALER UNDERCOAT (PSU 1) 1.3 <u>Fibre-cement:</u> Prime with PLASCON BONDING LIQUID (CVI 14). 2. PREVIOUSLY PAINTED SURFACES 2.1 <u>Previously painted surfaces in good condition:</u> Remove loose and flaking paint back to a sound substrate and a firm edge by scraping and sanding. Clean with POLYCELL SUGAR SOAP POWDER solution to remove all contaminants and chalked material. Rinse with clean water to remove all traces of sugar soap. Alternatively, clean with high pressure water jet. Allow to dry. Spot prime bare areas with appropriate primer. Sand glossy enamel surfaces to a matt finish and apply one coat of TRUE COLOUR 3 IN 1 PRIMER SEALER UNDERCOAT (PSU 1) 2.2 <u>Previously painted surfaces in poor condition:</u> Completely remove paint by most appropriate means e.g. scraping, coarse sanding. Wash thoroughly with POLYCELL SUGAR SOAP. Rinse well with fresh water to remove all traces of the cleaning agents and debris. Ensure substrate is sound, not powdery or friable, prior to coating. Proceed as for NEW WORK. 3. FILLING Fill all defects with the suitable POLYFILLA FILLER. Spot prime filled areas with TRUE COLOUR 3 IN 1 PRIMER SEALER UNDERCOAT (PSU 1).
Application	<ul style="list-style-type: none"> • Apply two or more coats to suitably prepared and primed surfaces to achieve complete obliteration. • Always maintain a wet edge and avoid downing tools during the application process to prevent lap marks and variances in colour or texture. Work from corner to corner or from a natural cut off point to another. Do not attempt touch ups but redo complete panels.
Cautions	<ul style="list-style-type: none"> • NOT recommended for use as a base coat under superior coatings due to possible loss of adhesion. • Full opacity is only achieved when dry. • Avoid painting during inclement weather or if temperature is below 10 °C.
Safety Precautions	<ul style="list-style-type: none"> • Keep out of reach of children. • Ensure good ventilation during application and drying. • In case of skin contact, wash with soap and water or a recognised skin cleaner. • Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist. • Harmful if swallowed. Do not induce vomiting. Seek medical attention. • Refer to Safety Data Sheet for complete information.

DISCLAIMER:

The recommendations contained herein are given in all good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control. **N.B.** Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging and colour.

KANSAI PLASCON (PTY) LIMITED

10 Frederick Cooper Drive,
Factoria, Krugersdorp
South Africa
1739.
Tel: +27 11 951 4500
Fax: +27 800 110 932

PLASCON ADVISORY SERVICE: 0860 20 40 60

EMAIL: advice@kansaiplascon.co.za

