

CATALYST FOR PLASCOGUARD 4000 HB FLOOR COATING

PRODUCT CODE: KAT 521

TECHNICAL DATA SHEET

Product Description	Cycloaliphatic amine catalyst for 2 pack epoxy systems.	
Intended Uses	Used to catalyse the PLASCOGUARD 4000 HB FLOOR COATING range (FHB 4000).	
Product Information	Appearance:	Colourless liquid
	SG at 23°C:	1.03 kg/L (typical)
	Flashpoint (closed cup):	96 °C
Application Details	Mixing	Mixing Ratio: 3 parts PLASCOGUARD 4000 (FHB 4000) to 1 part (KAT 521) by volume
Storage and Packaging:	Should be stored indoors in the original, unopened and undamaged container, in a dry place at a temperature not exceeding 30 °C. Exposure to direct sunlight should be avoided.	
Safety Precautions	<ul style="list-style-type: none">• Flammable - Keep away from source of ignition, flames, sparks and heat.• Use only in well ventilated environments.• Do not smoke during use.• Keep out of reach of children.• Dangerous if swallowed. Seek medical attention immediately.• Do not induce vomiting.• Avoid contact with skin and eyes.• Do not dispose of into natural water-ways or drainage system.• Refer to Safety Data Sheet for complete information.	

DISCLAIMER:

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

NB: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging and colour.

KANSAI PLASCON (PTY) LIMITED

10 Frederick Cooper Drive,
Factoria, Krugersdorp,
1739.

Tel: 011 951 4500

Fax: 0800 110 932

PLASCON ADVISORY SERVICE: 0860 20 40 60

EMAIL: advice@kansaiplascon.co.za