

CATALYST FOR PLASCOGUARD GEHOPON 7 SEALER GREEN

PRODUCT CODE: KAT 550

TECHNICAL DATA SHEET

Product Description	Amino polyamide resin solution catalyst		
Intended Uses	Used to catalyse the GW 7 PLASCOGUARD GEHOPON 7 SEALER GREEN		
Product Information	Colour:	Water white/Clear	
	Specific Gravity:	0.94	
	Pot Life:	16 hours @ 25 ºC	
Application Details	Mixing	Mixing Ratio: 5 parts GW 7 to 1 part KAT 550 by mass	
Storage and Packaging:	Should be stored indoors in the original, unopened and undamaged container, in a dry place at a temperature		
	not exceeding 30°C. Exposure to direct sunlight should be avoided.		
Cautions	This material is flammable.		
	Do not inhale vapours.		
Safety Precautions	Keep out of reach of children.		
	Ensure good ventilation during application and drying.		
	 In case of skin contact, wash with soap and water or a recognised skin cleaner. 		
	Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical		
	advice if symptoms persist.		
	Harmful if swallowed. Do not induce vomiting. Seek medical attention.		
	 Do not smoke whi 	Do not smoke while painting.	
	Flammable. Store in a cool dry place away from heat and sparks.		
	Refer to Safety Data Sheet for complete information		

DISCLAIMER:

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

NB: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging and colour.

KANSAI PLASCON (PTY) LIMITED

10 Frederick Cooper Drive, Factoria, Mogale City, 1739.

Tel: 011 951 4500 Fax: 0800 110 932

PLASCON ADVISORY SERVICE: 0860 20 40 60

EMAIL: advice@kansaiplascon.co.za



TDS: KAT 550 Version: 1.00 Revision date: 13/07/2015 Page 1 of 1