



PA 10 - THINNER

PRODUCT CODE: CTH 5

TECHNICAL DATA SHEET

Product description	Alcohol solvent blend.	
Intended Uses	<ul style="list-style-type: none">• Dilution of solvent borne etch primers.	
Features & Benefits	<ul style="list-style-type: none">• Fast evaporation.• Fast viscosity reduction.• High solvent power.	
Product Information	Appearance	Liquid
	Colours	Clear
	S G	0.770-0.820 g/ml
	Flash Point	13 °C
Storage & Packaging	Store separately from any reactive substances-Oxidisers in particular. Keep away from ignition sources.No smoking.No sparks. Store away from direct sun and heat . Avoid free fall of liquid - <u>use earthing</u> . Packaging: 5L and 200 L.	
Safety Precautions	<ul style="list-style-type: none">• Always keep out of reach of children.• Ensure good ventilation during handling.• In case of skin contact, wash with soap and water or a recognised skin cleaner.• Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist.• Harmful if swallowed or inhaled Do not induce vomiting. Seek medical attention.• Do not smoke while handling• Highly flammable. Store in a cool dry place away from heat and sparks.• Refer to Safety Data Sheet for complete information	

DISCLAIMER:

The recommendations contained herein are given in all good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

N.B. Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

N.B. TO ORDER: Quote product name, product code number, packaging and colour.

KANSAI PLASCON (PTY) LIMITED

10 Frederick Cooper Drive,
Factoria, Krugersdorp
South Africa
1739.
Tel: +27 11 951 4500
Fax: +27 800 110 932

PLASCON ADVISORY SERVICE: 0860 20 40 60

EMAIL: advice@kansaiplascon.co.za

