

## FAST DRYING SOLVENT

PRODUCT CODE: PYY 1

### TECHNICAL DATA SHEET

<b>Product Description</b>	A blend of fast drying organic solvents for use as specified.	
<b>Intended Uses</b>	<ul style="list-style-type: none"> <li>To thin enamel based Industrial topcoats and primers, for fast drying applications.</li> <li>To clean equipment e.g. paint rollers, brushes etc.</li> </ul>	
<b>Product Information</b>	Appearance	Colourless liquid
	Type	Hydrocarbon solvents
	S G at 23°C	0,78 kg /L (typical)
	Flash Point	2 °C (typical Closed Cup)
<b>Application Details</b>	Mixing	Use in the proportion as specified.
<b>Storage and Packaging</b>	Store away from direct sun, open flames, sparks and severe cold. 200 L, 25 L	
<b>Cautions</b>	<ul style="list-style-type: none"> <li>See recommendations on specific industrial finished product data sheets</li> </ul>	
<b>Safety</b>	<ul style="list-style-type: none"> <li>Flammable - Keep away from source of ignition, flames, sparks and heat.</li> <li>Use only in well ventilated environments.</li> <li>Do not smoke during use.</li> <li>Keep out of reach of children.</li> <li>Dangerous if swallowed. Seek medical attention immediately. Do not induce vomiting.</li> <li>Avoid contact with skin and eyes.</li> <li>Do not dispose of into natural water-ways or drainage system.</li> <li>Refer to Safety Data Sheet for complete information</li> </ul>	
<b>Precautions</b>		

#### **DISCLAIMER:**

The recommendations contained herein are given in all good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

**N.B:** Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

**NB: TO ORDER:** Quote product name, product code number, packaging and colour.

#### **KANSAI PLASCON (PTY) LTD**

10 Frederick Cooper Drive,  
Factoria, Krugersdorp  
South Africa  
1739.  
Tel: +27 11 951 4500  
Fax: +27 800 110 932

**PLASCON ADVISORY SERVICE:** 0860 20 40 60

**EMAIL:** advice@kansaiplascon.co.za