

# **COASTCOTE THINNER**

## **PRODUCT CODE: SNK 7**

### **TECHNICAL DATA SHEET**

Product Description	A blend of aromatic hydrocarbons and alcohols for use as specified.	
Intended Uses	<ul> <li>Used to thin COATCOTE ETCH PRIMER (SNK Range) and LC ETCH PRIMER (SN Range) for spray application. (Refer to relevant SNK and SN Range TDS)</li> <li>Used to thin various products prior to application, as specified.</li> <li>To clean equipment e.g. paint rollers, brushes etc.</li> </ul>	
Product Information	Appearance Type Odour Boiling Range S G Flash Point	Colourless liquid Blend of aromatic hydrocarbons and alcohol Aromatic 77 to 147 °C (Reef) 0,830 (typical) < 23 °C (typical)
Application Details	Mixing	Use in the proportion as specified.
Storage and Packaging	Store away from direct sun, open flames, sparks and severe cold. 200 L, 25 L and 5 L	
Cautions	<ul> <li>Not recommended for thinning high gloss brushing enamels, since it may cause lifting of the previous coat.</li> </ul>	
Safety Precautions	<ul> <li>Flammable - Keep away from source of ignition, flames, sparks and heat.</li> <li>Use only in well ventilated environments.</li> <li>Do not smoke during use.</li> <li>Keep out of reach of children.</li> <li>Dangerous if swallowed. Seek medical attention immediately.</li> <li>Do not induce vomiting.</li> <li>Avoid contact with skin and eyes.</li> <li>Do not dispose of into natural water-ways or drainage system.</li> <li>Refer to Safety Data Sheet for complete information</li> </ul>	

#### DISCLAIMER:

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

**N.B.** Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

N.B. TO ORDER: Quote product name, product code number, packaging and colour

#### KANSAI PLASCON (PTY) LTD

10 Frederick Cooper Drive, Factoria, Krugersdorp South Africa 1739. Tel: +27 11 951 4500 Fax: +27 800 110 932

PLASCON ADVISORY SERVICE: 0860 20 40 60 EMAIL: advice@kansaiplascon.co.za

