

EPIWASH THINNER

PRODUCT CODE: TH 128

TECHNICAL DATA SHEET

Product Description	Epoxy Thinner
Intended Uses	Formulated for use with Epiwash Primer range Can also be used with rust inhibitive epoxy primer (SAT 356)
Features	 Fast evaporation High solvency power
Product Information	AppearanceLiquidColourClearS G0,81-0,85Flash Point< 23 °C
Storage and Packaging	 Store in a cool place away from direct sunlight. Keep away from sources of ignition, open flames and sparks Packaging: 5 L, 25 L and 200 L
Safety Precautions	 Always keep solvent out of reach of children. Ensure good ventilation during application and drying. If accidental contact with skin should occur, wash immediately with soap and water or a recognised skin cleaner. Take care to avoid contact with the eyes. In case of contact, immediately rinse the eyes with plenty of water and seek medical attention. Harmful if swallowed. Seek medical attention and do not induce vomiting. Do not smoke while applying or mixing product. Flammable. Store in a cool dry place away from heat and sparks. Refer to Safety Data Sheet for complete information.

DISCLAIMER:

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

N.B.: Technology may change with time necessitating changes to this Product Data Sheet (PDS). It is the responsibility of the user to ensure that the latest PDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging and colour.

KANSAI PLASCON (PTY) LTD

10 Frederick Cooper Drive, Factoria, Krugersdorp South Africa 1739. Tel: +27 11 951 4500 Fax: +27 800 110 932

PLASCON ADVISORY SERVICE: 0860 20 40 60 EMAIL: advice@kansaiplascon.co.za

