

TRADEPRO UNDERCOAT (UWU 1)

Section 1. Identification

GHS product identifier : TradePro Undercoat (UWU 1)

Other means of identification: An alkyd based undercoat for general interior and exterior use.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Provides good adhesion to most types of primers. May be overcoated by a

variety of alkyd and emulsion based topcoat systems. Used as a general purpose undercoat on previously painted or suitably primed plaster, wood,

metal, etc.

Supplier's details : Kansai Plascon (Pty) Ltd

P.O. Box 4010 Luipaardsvlei

1743

Emergency phone : (011) 951 4500 (within hours of operation)

Facsimile : (011) 955 2841 National Contact Person : Mr C. Costa

Section 2. Hazards identification

Classification of the : FLAMMABLE LIQUID- Category 3

substance or mixture SKIN CORROSION/ IRRITATION- Category 2

ACUTE TOXICITY- Category 4

SERIOUS EYE DAMAGE/ IRRITATION- Category 2

ASPIRATION TOXICITY- Category 1

AQUATIC TOXICITY CHRONIC- Category 2

Label elements according to : SANS 10234: 2008

Hazard pictograms :









Signal word : Danger

Hazard statements : H226- Flammable liquid and vapour.

H303- May be harmful if swallowed.

H304- May be fatal if swallowed and enters airways

H315- Causes skin irritation. H320- Causes eye irritiation

H332- Harmful if inhaled

H411- Toxic to aquatic life with long-lasting effects.



Product code: TradePro Undercoat (UWU 1) Date of revision: 17/07/2017 Version: 1 Page 1 of 12



TRADEPRO UNDERCOAT (UWU 1)

Precautionary statements

General : P101- If medical advice is needed, have product container or label at hand.

P102- Keep out of reach of children.

P103- Read label before use.

Prevention : P202- Do not handle until all safety precautions have been read and

understood.

P501: Dispose of contents/containers in accordance with local

regulation.

P233- Keep container tightly closed.

P261- Avoid breathing vapours/spray.

P262- Do not get in eyes, on skin, or on clothing.

P270- Do not eat, drink or smoke when using this product.

P271- Use only outdoors or in a well-ventilated area.

P273- Avoid release to the environment.

P280- Wear protective gloves/protective clothing/eye protection/face

protection.

P285- In case of inadequate ventilation wear respiratory protection.

P235+410- Keep cool. Protect from sunlight

: P314- Get medical advice/attention if you feel unwell. Response

P391- Collect spillage.

P301+330+331- IF SWALLOWED- Rinse mouth. Do NOT induce vomiting.

P303+361+353- IF ON SKIN (or hair)- Take off immediately all

contaminated clothing. Rinse skin with water/ shower.

P304+340: IF INHALED- Remove person to fresh air and keep comfortable

for breathing.

P305+351+338- IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses if present and easy to do - continue

rinsing.

P333+313- If skin irritation or a rash occurs: Get medical advice/attention.

P337+313- If eye irritation persists get medical advice/attention.

P361+364- Take off immediately all contaminated clothing and wash it

before reuse.

P362+364- Take off contaminated clothing and wash it before reuse.



Product code: TradePro Undercoat (UWU 1) Date of revision: 17/07/2017 Version: 1 Page **2** of **12**



conforms to SANS ISO 11014: 2010 and ISO 11014: 2009

TRADEPRO UNDERCOAT (UWU 1)

P370+380- In case of fire: Evacuate area.

Storage : P410- Protect from sunlight.

P402+404- Store in a dry place. Store in a closed container.

P403+235- Store in a well ventilated place. Keep cool.

Other hazards which do not

Result in classification : None identified

Section 3. Composition/information on ingredients

Subtance/mixture : Mixture

Other means of identification : Alkyd based coating

CAS number/other identifiers

CAS number : Not applicable

Ingredient name	CAS number	%	SANS 10234 Classification
Medium Aliphatic Petroleum Solvent	64742-88-7	10.0-20.0	Acute Tox. 4, H332 Acute Tox. 5, H303 Asp. Tox 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2B, H320 Aquatic Chronic 2, H411 Flam. Liq. 3, H226
Heavy Aromatic Petroleum Solvent	64742-94-5	<10.0	Acute Tox. 4, H332 Acute Tox. 5, H303 Asp. Tox 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2B, H320 Aquatic Chronic 2, H411 Flam. Liq. 3, H226

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper

and lower eyelids. Check for and remove any contact lenses. Get medical

attention if irritation persist.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for

breathing. Get medical attention if symptoms occur.

Skin contact : Wash contaminated skin with soap or a recognised skin cleaner and plenty

of water. Avoid the use of solvents. Remove contaminated clothing and

shoes. Get medical attention if symptoms persist.

Product code: TradePro Undercoat (UWU 1) Date of revision: 17/07/2017 Version: 1 Page 3 of 12



conforms to SANS ISO 11014: 2010 and ISO 11014: 2009

TRADEPRO UNDERCOAT (UWU 1)

Ingestion : Wash out mouth with water. Remove victim to fresh air and keep at rest in

a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get

medical attention if symptoms occur.

Most important symptoms/ effects, acute and delayed

Potential acute health effects

Eye contact : May cause moderate irritation.

Inhalation : Harmful if inhaled. Irritating and narcotic. Can affect central nervous system.

Skin contact : Irritating if in contact with skin. Risk of dermatitis. Ingestion : Harmful. May cause lung damage if swallowed.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include pain or irritation, watering or redness.

Inhalation : Adverse symptoms may include nausea or vomiting, headache,

drowsiness/fatigue or dizziness/vertigo.

Skin contact : Adverse symptoms may include irritation or redness.

Ingestion : May cause damage to organs through prolonged or repeated exposure.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if

large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable

training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire such as

foam, CO2 or dry powder. Use fog to cool and control.

Unsuitable extinguishing media: Do NOT use water jets.

Specific hazards arising

from the chemical : In a fire or if heated, a pressure increase will occur and the container may

burst. Can form explosive vapour/air mixture. Static discharge hazard.

Flammable with toxic fumes. Cool containers in case of fire.

Hazardous thermal

decomposition products : Decomposition products may include the following materials:

carbon dioxide carbon monoxide metal oxide/oxides



Product code: TradePro Undercoat (UWU 1) Date of revision: 17/07/2017 Version: 1 Page 4 of 12



conforms to SANS ISO 11014: 2010 and ISO 11014: 2009

TRADEPRO UNDERCOAT (UWU 1)

Special protective actions

For fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self contained breathing apparatus (SCBA) with a full face-piece operated in

positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders

: Ensure sufficient ventilation. Remove all ignition sources. If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.

Product code: TradePro Undercoat (UWU 1) Date of revision: 17/07/2017 Version: 1 Page 5 of 12



onforms to SANS ISO 11014: 2010 and ISO 11014: 2009

TRADEPRO UNDERCOAT (UWU 1)

Remove contaminated clothing and protective equipment before entering eating areas. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep away from ignition sources. No open flames. No smoking. Avoid free fall of liquid – use earthing.

Conditions for safe storage, Including any Incompatibilities

:Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Do not reuse container.

Section 8. Exposure controls/personal protection

Occupational exposure limits:

Ingredient name	Exposure limits
Heavy Aromatic Petroleum Solvent	ACGIH TLV:
	TWA: 525 mg/m3
	TWA: 100ppm

Recommended monitoring Procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Appropriate engineering controls

: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.



Product code: TradePro Undercoat (UWU 1) Date of revision: 17/07/2017 Version: 1 Page 6 of 12



conforms to SANS ISO 11014: 2010 and ISO 11014: 2009

TRADEPRO UNDERCOAT (UWU 1)

Eye/face protection : Avoid direct contact. Never touch eyes with dirty hands or gloves. Safety

eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid

splashes, mists, gases or dusts.

Hand protection : Avoid direct contact. Chemical-resistant, impervious gloves complying

with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Body protection : Personal protective equipment for the body should be selected based on

the task being performed and the risks involved and should be approved

by a specialist before handling this product.

Other skin protection : Avoid direct contact. Appropriate footwear and any additional skin protection

Measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator with organic vapour

filter cartridge (e.g. A1B1E1 type) complying with an approved standard if a risk assessment indicates this is necessary e.g. in case of insufficient ventilation. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of

the selected respirator.

Section 9. Physical and chemical properties

Physical state : Viscous Liquid

Colour : White

Odor : No data available.

Odor threshold : No data available.

pH : Not applicable.

Melting point : No data available.

Boiling point : No data available.

Flash point : > 23 °C

Evaporation rate : No data available.

Flammability (solid, gas) : Not applicable.

Lower and upper explosive

(flammable) limits : Not applicable.

Vapor pressure : No data available.

Vapor density : No data available.

PLASCON

Product code: TradePro Undercoat (UWU 1) Date of revision: 17/07/2017 Version: 1 Page 7 of 12



conforms to SANS ISO 11014; 2010 and ISO 11014; 2009

TRADEPRO UNDERCOAT (UWU 1)

Relative density : 1.42 (typical)

Solubility : Soluble in organic solvents, insoluble in water.

Partition coefficient,

n-octanol/water : No data available.

Auto-ignition temperature : No data available.

Decomposition temperature : No data available.

Viscosity : 80 - 90 KU

Section 10. Stability and reactivity

Reactivity: Inert - no reaction with fire-fighting water.

Chemical stability: Stable under normal conditions.

Possibility of hazardous

reactions : Under normal conditions of storage and use, hazardous reactions will not

occur.

Conditions to avoid : Could generate static – Use earthing. Avoid all possible sources of ignition

(spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or

expose containers to heat or sources of ignition.

Incompatible materials : Any reactive substances – oxidisers in particular.

Hazardous decomposition

products: Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Section 11. Toxicological information

Acute Toxicity

No data available.

Irritation/Corrosion

No data available.

Specific target organ toxicity (single exposure)

No data available.

Specific target organ toxicity (repeated exposure)

No data available.

Aspiration hazard

Name	Result ASPIRATION HAZARD - Category 1	
Medium Aliphatic Petroleum Solvent		
Heavy Aromatic Petroleum Solvent	ASPIRATION HAZARD - Category 1	



Product code: TradePro Undercoat (UWU 1) Date of revision: 17/07/2017 Version: 1 Page 8 of 12



onforms to SANS ISO 11014: 2010 and ISO 11014: 2009

TRADEPRO UNDERCOAT (UWU 1)

Information on the likely

routes of exposure : Inhalation, skin contact

Potential acute health effects

Eye contact : May cause moderate irritation.

Inhalation : Harmful if inhaled. Irritating and narcotic. Can affect central nervous system.

Skin contact : Irritating if in contact with skin. Risk of dermatitis. Ingestion : Harmful. May cause lung damage if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include pain or irritation, watering or redness.

Inhalation : Adverse symptoms may include nausea or vomiting, headache,

drowsiness/fatigue or dizziness/vertigo.

Skin contact : Adverse symptoms may include irritation or redness.

Ingestion : May cause damage to organs through prolonged or repeated exposure.

Potential Chronic health effects

General : Once sensitized, a severe allergic reaction may occur when subsequently

exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

No known significant effects or critical hazards.

Acute toxicity estimates No data available.

Section 12. Ecological information

Toxicity

No data available.

Persistence and degradability

No data available.

Bioaccumalitive potential

No data available.

Mobility in soil

Soil/ water partition coefficient

(Koc) : No data available.Mobility : No data available.

PBT/vPvB data : P: No data available. B: No data available. T: No data available.

Other adverse effects : No known significant effects or critical hazards.



Product code: TradePro Undercoat (UWU 1) Date of revision: 17/07/2017 Version: 1 Page 9 of 12



Conforms to SANS ISO 11014: 2010 and ISO 11014: 2009

TRADEPRO UNDERCOAT (UWU 1)

Section 13. Disposal considerations

Disposal methods

: This material and its container must be disposed of in a safe way. The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor – potential for spontaneous combustion. Take care with used containers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	Transportation - road - SANS 10228:2012	Transportation- Maritime - IMO/ IMDG	Transportation- Air - IATA
UN number	1263	1263	1263
UN proper shipping	Paint related material	Paint related material	Paint related material
name			
Transport hazard class(es)	FLAMMABLE 3	FLAMMABLE 3	FLAMMABLE 3
Packing group	III	III	III
Marine pollutant	No	No	No
Additional information	No data available	Emergency schedules (EmS) F-A, S-F	Passenger and Cargo Aircraft Quantity limitation: 450 L Packaging instructions: 964 Cargo Aircraft Only Quantity limitation: 450 L Packaging instructions: 964 Limited Quantities - Passenger Aircraft Quantity limitation: 30 kg Packaging instructions: Y964



Product code: TradePro Undercoat (UWU 1) Date of revision: 17/07/2017 Version: 1 Page 10 of 12



conforms to SANS ISO 11014: 2010 and ISO 11014: 2009

TRADEPRO UNDERCOAT (UWU 1)

Transport in bulk	No data available	No data available	No data available
according to Annex II			
of MARPOL 73/78 and			
the IBC code			

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

: Relevant information regarding authorization: Occupational Health and Safety Act 1993 Regulation for Hazardous Chemical Substances.

Relevant information regarding restrictions: None known. **EU regulations:** Regulation EC 1272/2008 [EU-GHS/CLP] and EU

directives 67/548/EEC or EC 1999/45/EC

Other National regulations: None. Standards used for PPE recommendations in Section 8: NIOSH-National Institute for Occupational Health and Safety (USA) EN 166- European standard which concerns the area of eye protection. EN 374-3 European standards for permeation and penetration. EN 141/EN 143 European standards for gas mixtures to remove specified gases and vapours or combined filters for removing solids, and/or liquid particles and specified gases and vapours.

Section 16. Other information

History

Date of printing : 17/07/2017
Date of previous issue : Not applicable

Key to abbreviations : ATE = Acute Toxicity Estimate

BCP Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

RID = The Regulations concerning the International Carriage of Dangerous

Goods by Rail UN = United Nations

References : Supplier safety data sheets

Further information:

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

PLASCON

Product code: TradePro Undercoat (UWU 1) Date of revision: 17/07/2017 Version: 1 Page 11 of 12



onforms to SANS ISO 11014: 2010 and ISO 11014: 2009

TRADEPRO UNDERCOAT (UWU 1)

Notice to readers:

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees.

This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Legal disclaimer:

The above information is believed to be correct but does not purport to be all inclusive and shall be only used as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.



Product code: TradePro Undercoat (UWU 1) Date of revision: 17/07/2017 Version: 1 Page 12 of 12