

Safety Data Sheet

According to UN GHS

Date of Issue: 30/08/2022 Revision Date 30/08/2022 | Version 2.0

Product name

FLOORTECT 4000 SF CURING AGENT



PLASCOGUARD 4000 HB CURING AGENT(KAT 521)

SECTION 1: IDENTIFICATION

GHS product identifier : FLOORTECT 4000 SF CURING AGENT(KAT 521)

Other means of identification: Cycloaliphatic amine catalyst for 2 pack epoxy systems.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Curing agent for FLOORTECT 4000 SF(FHB 4000)

Restrictions of use : Do not use in areas / substrates other than specified for in

identified uses / TDS.

Supplier's details : Kansai Plascon (Pty) Ltd

P.O. Box 4010 Luipaardsvlei

1743

Emergency phone : +2711 951 4500 (within hours of operation)

Cell phone : +2783 991 5782 (outside hours of operation)

Facsimile : +2711 955 2841
National Contact Person : Misheck Mundondo



Page 1 of 15 Part of KANSAI PAINT



(KAT 521)

UN2289 ISOPHERONEDIAMINE

Safety Data Sheet

Date of Issue: 30/08/2022 Revision Date 30/08/2022 \mid Version 2.0

SECTION 2: HAZARDOUS IDENTIFICATION

Classification of the

substance or mixture : SKIN CORROSION/ IRRITATION - Category 1B

SKIN SENSITIZATION - Category 1

ACUTE TOXICITY (DERMAL) - Category 4
ACUTE TOXICITY (ORAL) - Category 4

ACUTE TOXICITY (INHALATION) - Category 4 AQUATIC TOXICITY (CHRONIC) - Category 2

Label elements according to : UN GHS

Hazard pictograms :



Signal word : Danger

Hazard statements : H302 - Harmful if swallowed.

H312 - Harmful if in contact with skin.

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H332 - Harmful if inhaled.

H411 - Toxic to aquatic life with long-lasting effects.

Precautionary statements

General

: P101 - If medical advice is needed, have product container or

label at hand.

P102 - Keep out of reach of children.

P103 - Read carefully and follow all instructions.

Prevention : P260 - Do not breathe vapor.

P261 - Avoid breathing dust/fumes/gas/mist/vapours/spray.

P264 - Wash hands thoroughly after handling.

P272 - Contaminated work clothing should not be allowed out

of the workplace.

P270 - Do not eat, drink, or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, eye

protection or face protection.

P283 - Wear fire/flame resistant/retardant clothing.



Page 2 of 15 Part of KANSAI PAINT



(KAT 521)

UN2289 ISOPHERONEDIAMINE

Safety Data Sheet

Date of Issue: 30/08/2022 Revision Date 30/08/2022 | Version 2.0

Response : P391 - Collect spillage. Hazardous to the aquatic environment.

P301+313 - IF SWALLOWED: Get medical advice/attention.

P302+352 - IF ON SKIN: Wash with plenty of water.

P301+330+331 - IF SWALLOWED - Rinse mouth. Do NOT

induce vomiting.

P303+361+353 - IF ON SKIN (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower.

P304+340 - IF INHALED: Remove person to fresh air and keep

comfortable for breathing.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to

do – continue rinsing.

P333+313 - If skin irritation or a rash occurs: Get medical

advice/attention.

Storage : P405 – Store locked up.

Disposal : P501 - Dispose of contents/containers in accordance with local

regulation

Other hazards which do not

result in classification : None identified.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Substance/mixture : Mixture

Other means of identification : Cycloaliphatic amine catalyst for 2 pack epoxy systems.

CAS number/other identifiers

CAS number : Not applicable.

Ingredient name	CAS number	%	UN GHS Classification
Benzyl Alcohol	100-51-6	70.0-80.0	Acute Tox. 4, H302
			Acute Tox. 4, H332
Cycloaliphatic amine	Not Available	40.0-50.0	Aquatic Chronic. 2, H411
Isophoronediamine	2855-13-2	30.0-40.0	Skin Corr. 1, H314 Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Sens. 1, H317 Aquatic Chronic.3, H412

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and



Page 3 of 15 Part of KANSAI PAINT



(KAT 521)

UN2289 ISOPHERONEDIAMINE

Safety Data Sheet

Date of Issue: 30/08/2022 Revision Date 30/08/2022 \mid Version 2.0

hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: FIRST AID MEASURES

Description of necessary first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting

the upper and lower eyelids. Check for and remove any contact

lenses. Get medical attention if irritation persist.

Inhalation : Remove victim to fresh air and keep at rest in a position

comfortable for breathing. Get medical attention if symptoms

occur.

Skin contact : Remove contaminated clothing and shoes. Wash contaminated

skin with soap or a recognised skin cleaner and plenty of water. Avoid the use of solvents. Get medical attention if symptoms persist. Wash clothing before reuse. Clean shoes

thoroughly before reuse.

Ingestion : Remove victim to fresh air and keep at rest in a position

comfortable for breathing. Wash out mouth with water.

Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe.

Most important symptoms/ effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Harmful if inhaled. May cause respiratory irritation. May cause

drowsiness or dizziness.

Skin contact : Harmful in contact with skin. Causes skin irritation.

Ingestion : Harmful if swallowed.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include pain or irritation, watering or

redness.

Inhalation : Adverse symptoms may include nausea or vomiting,



Page 4 of 15 Part of KANSAI PAINT



(KAT 521)

UN2289 ISOPHERONEDIAMINE

Safety Data Sheet

Date of Issue: 30/08/2022 Revision Date 30/08/2022 | Version 2.0

headache.

Skin contact : Adverse symptoms may include irritation or redness.

Ingestion : Adverse symptoms may include nausea or vomiting,

headache.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first aiders : No action shall be taken involving any personal risk or without

Suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained

breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash

contaminated clothing thoroughly with water before removing it,

or wear gloves.

See toxicological information (Section 11)

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire

such as dry powder, CO2, water spray (fog) or foam. Use fog

to cool and control.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from

from the chemical

: Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of

a subsequent explosion. Runoff to sewer may create fire or explosion hazard. Fire water contaminated with this material must be contained and prevented from being discharged to any

waterway, sewer or drain.

Hazardous thermal decomposition products

: Decomposition products may include the following materials

carbon dioxide carbon monoxide metal oxide/oxides



Page 5 of 15 Part of KANSAI PAINT



(KAT 521)

UN2289 ISOPHERONEDIAMINE

Safety Data Sheet

Date of Issue: 30/08/2022 Revision Date 30/08/2022 | Version 2.0

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face piece operated in positive pressure mode.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

For non-emergency

personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk-through spilled material. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil, or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant



Page 6 of 15 Part of KANSAI PAINT



UN2289 ISOPHERONEDIAMINE

Safety Data Sheet

Date of Issue: 30/08/2022 Revision Date 30/08/2022 | Version 2.0

or proceed as follows. Contain and collect spillage with non combustible, absorbent material e.g., sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored, and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Store and use away from heat, sparks, open flame, or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool, and well ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Do not reuse container.



Page 7 of 15 Part of KANSAI PAINT



UN2289 ISOPHERONEDIAMINE

Safety Data Sheet

Date of Issue: 30/08/2022 Revision Date 30/08/2022 \mid Version 2.0

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure limits

Ingredient name	Exposure limits
Benzyl Alcohol	WEEL:
	TWA: 10 ppm; 44 mg/m ³

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Appropriate engineering controls

: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters, or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms, and face thoroughly after handling chemical products, before eating, smoking, and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Avoid direct contact. Never touch eyes with dirty hands or gloves. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.



Page 8 of 15 Part of KANSAI PAINT



(KAT 521)

UN2289 ISOPHERONEDIAMINE

Safety Data Sheet

Date of Issue: 30/08/2022 Revision Date 30/08/2022 | Version 2.0

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be always worn when handling chemical products if a risk assessment indicates this is

necessary.

Body protection : Personal protective equipment for the body should be selected

based on the task being performed and the risks involved and

should be approved by a specialist before handling this

product.

Other skin protection : Appropriate footwear and any additional skin protection

measures should be selected based on the task being

performed and the risks involved and should be approved by a

specialist before handling this product.

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator

complying with an approved standard if a risk assessment

indicates this is necessary e.g., in case of insufficient

ventilation. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the

safe working limits of the selected respirator.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Liquid

Colour : Colourless

Odour (Threshold) : No data available

Melting point : Not applicable

Boiling point : 205°C

Flammability (gas, liquid, solid) : No data available

Lower and upper explosive

(flammable) limits : No data available

Flash point : 96°C

Auto-ignition Temperature : No data available



Page 9 of 15 Part of KANSAI PAINT



(KAT 521)

UN2289 ISOPHERONEDIAMINE

Safety Data Sheet

Date of Issue: 30/08/2022 Revision Date 30/08/2022 | Version 2.0

Decomposition Temperature : No data available

pH : 9.0

Viscosity : No data available

Solubility : Soluble in organic solvents, insoluble in water

Partition coefficient,

n-octanol/water : No data available

Evaporation rate : No data available

Vapour pressure : <10.34mmHg at 21°C

Relative density : 1.03kg/l (typical)

Vapour density : No data available

Particle characteristics : No data available

SECTION 10: STABILITY AND REACTIVITY

Reactivity : No specific test data related to reactivity available for this

product or its ingredients.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions:

: Under normal conditions of storage and use, hazardous

reactions will not occur.

Conditions to avoid : No available data.

Incompatible materials : No available data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous

decomposition products should not be produced.

Page 10 of 15 Part of KANSAI PAINT



(KAT 521)

UN2289 ISOPHERONEDIAMINE

Safety Data Sheet

Date of Issue: 30/08/2022 Revision Date 30/08/2022 \mid Version 2.0

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity

Ingredient name	Result	Species	Dose	Exposure
Benzyl alcohol	LD50 Oral	Rat	2369 mg/kg	-
	LC50 Inhalation	Rat	>4.178	4 hours
	LD50 Dermal	Rabbit	>2000	-

Irritation/Corrosion

Ingredient name	Result	Species	Score	Exposure	Observation
Benzyl alcohol	Skin - Irritation	Rabbit	-	4 hours	Not irritant
	Eyes - Irritation	Rabbit	-	-	Irritant
Isophoronediamine	Skin - Irritation	Rabbit	-	24 hours	Causes burns
	Eyes - Irritation	Rabbit	-	24 hours	Corrosive

Specific target organ toxicity (single exposure)

No data available

Specific target organ toxicity (repeated exposure)

No data available

Aspiration hazard

No data available

Information on the likely

routes of exposure : Inhalation, skin, and eye contact.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Harmful if inhaled.

Skin contact : Causes severe skin burns. May cause an allergic skin reaction.

Ingestion : Harmful if swallowed.

Symptoms related to the physical, chemical, and toxicological characteristics

Eye contact : Adverse symptoms may include pain or irritation, watering or

redness.

Inhalation : Adverse symptoms may include nausea or vomiting, headache,

respiratory irritation, drowsiness/fatigue, or dizziness/vertigo.

Skin contact : Adverse symptoms may include irritation or redness.

Ingestion : Adverse symptoms may include nausea or vomiting, headache



Page 11 of 15 Part of KANSAI PAINT



(KAT 521)

UN2289 ISOPHERONEDIAMINE

Safety Data Sheet

Date of Issue: 30/08/2022 Revision Date 30/08/2022 | Version 2.0

Potential Chronic health effects

General : No known significant effects or critical hazards.
Carcinogenicity : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Teratogenicity : No known significant effects or critical hazards.
Developmental effects : No known significant effects or critical hazards.
Fertility effects : No known significant effects or critical hazards.

No known significant effects or critical hazards.

Acute toxicity estimates No data available

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ingredient name	Result	Species	Exposure
Benzyl alcohol	Acute LC50 10 mg/l	Fish - Bluegill sunfish	96 hours
	Acute LC50 460 mg/l	Fish - Fathead minnow	96 hours
	Acute IC50 700 mg/l	Algae - Green algae	72 hours

Persistence and degradability No data available.

Bio accumulative potential No data available.

Mobility in soil
Soil/ water partition

coefficient (KOC) : No data available.

Mobility : No data available.
PBT/vPvB data : P: No data available.
B: No data available.

T: No data available.

Other adverse effects : No known significant effects or critical hazards.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste



Page 12 of 15 Part of KANSAI PAINT



UN2289 ISOPHERONEDIAMINE

Safety Data Sheet

Date of Issue: 30/08/2022 Revision Date 30/08/2022 | Version 2.0

disposal contractor. Disposal of this product, solutions, and any by-products should always comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: TRANSPORT INFORMATION

	Transportation - road - SANS 10228:2012	Transportation- Maritime - IMO/ IMDG	Transportation- Air – IATA
UN number	2289	2289	2289
UN proper shipping name	Isophoronediamine Mixture	Isophoronediamine Mixture	Isophoronediamine Mixture
Transport hazard class(es)	CORROSIVE	CORROSIVE	CORROSIVE
Packing group	III	III	III
Environmental hazards	Environmentally hazardous	Marine pollutant	Environmentally hazardous
Additional information	No data available	Emergency schedules (EmS) F-A, S-B	No data available
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	No data available	No data available	No data available

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product

: Relevant information regarding authorization: Occupational

Page 13 of 15 Part of KANSAI PAINT



(KAT 521)

UN2289 ISOPHERONEDIAMINE

Safety Data Sheet

Date of Issue: 30/08/2022 Revision Date 30/08/2022 | Version 2.0

Health and Safety Act 1993 Regulation for Hazardous Chemical Substances. Relevant information regarding restrictions: None known. EU regulations: Regulation EC 1272/2008 [EU-GHS/CLP] and EU directives 67/548/EEC or EC 1999/45/EC Other National regulations: None. Standards used for PPE recommendations in Section 8: NIOSH-National Institute for Occupational Health and Safety (USA) EN 166 European standard which concerns the area of eye protection. EN 374-3 European standards for permeation and penetration. EN 141/EN 143 European standards for gas mixtures to remove specified gases and vapours or combined filters for removing solids, and/or liquid particles and specified gases and vapours.

SECTION 16: OTHER INFORMATION

History

Date of review : 30/08/2022

Date of review	Version	Amendments
30/08/2022	2.0	GHS Purple Book version 9 alignment
07/06/201 9	1.0	GHS compliant SDS

Date of previous issue : 07/06/2019

Key to abbreviations : ATE = Acute Toxicity Estimate

BCP Bioconcentration Factor

GHS = Globally Harmonized System of Classification and

Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of

1978. ("Marpol" = marine pollution)

OHSA = Occupational Health and Safety Act, 1993 (South

Africa)

RID = The Regulations concerning the International Carriage of

Dangerous Goods by Rail UN = United Nations



Page 14 of 15 Part of KANSAI PAINT



UN2289 ISOPHERONEDIAMINE

Safety Data Sheet

Date of Issue: 30/08/2022 Revision Date 30/08/2022 | Version 2.0

References : Supplier Safety Data Sheets.

Further information:

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Notice to readers:

Employers should use this information only as a supplement to other information gathered by them and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Legal disclaimer:

The above information is believed to be correct but does not purport to be all inclusive and shall be only used as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.



Page 15 of 15 Part of KANSAI PAINT