



## Safety Data Sheet

According to UN GHS

Date of Issue: 26/08/2022 Revision Date 26/08/2022 | Version 9.0

Product name

# STEELTECT 1500 SB

## EPIWASH STRONTIUM CHROMATE PRIMER (AW 255)



### SECTION 1: IDENTIFICATION

**GHS product identifier** : STEELTECT 1500 SB(AW 255)

**Other means of identification** : The base component of the premium quality dual pack strontium chromate epoxy primer.

### Relevant identified uses of the substance or mixture and uses advised against


**Identified uses** : Recommended as a primer for mild steel, galvanised iron, aluminium, stainless steel, fibreglass, and various alloys. Ideal for earth moving equipment, military vehicles, trucks, and bus bodies (particularly where both mild steel and aluminium components are used) fibre glass canopies. Suitable as a primer over Electro-coat.

**Restrictions of use** : Do not use in areas / substrates other than specified for in identified uses / TDS.

**Supplier's details** : Kansai Plascon (Pty) Ltd  
P.O. Box 4010  
Luipaardsvlei  
1743

**Emergency phone** : +2711 951 4500 (within hours of operation)  
**Cell phone** : +2783 991 5782 (outside hours of operation)  
**Facsimile** : +2711 955 2841  
**National Contact Person** : Misheck Mundondo

## SECTION 2: HAZARDOUS IDENTIFICATION

<b>Classification of the substance or mixture</b>	: FLAMMABLE LIQUID - Category 2 SERIOUS EYE DAMAGE/ IRRITATION - Category 2 SKIN CORROSION/IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY SINGLE EXPOSURE – Category 3 ACUTE TOXICITY (DERMAL) – Category 3 ACUTE TOXICITY (ORAL - Category 3 ACUTE TOXICITY (INHALATION) – Category 3 AQUATIC TOXICITY (ACUTE) – Category 2 AQUATIC TOXICITY (CHRONIC) - Category 1 SKIN SENSITIZATION - Category 1
<b>Label elements according to</b>	: UN GHS
<b>Hazard pictograms</b>	: 
<b>Signal word</b>	: Danger
<b>Hazard statements</b>	: H225 - Highly flammable liquid and vapour. H301 - Toxic if swallowed. H311 - Toxic in contact with skin. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes eye irritation. H331 - Toxic if inhaled. H336 - May cause drowsiness or dizziness. H400 - Very toxic to aquatic life H411 - Toxic to aquatic life with long-lasting effects.
<b>Precautionary statements</b>	
<b>General</b>	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P103 - Read carefully and follow all instructions.
<b>Prevention</b>	: P201 - Obtain special instructions before use. P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P202 - Do not handle until all safety precautions have been read and understood  
P240 - Ground/bond container and receiving equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P260 - Do not breathe vapor.  
P261 - Avoid breathing dust/fumes/gas/mist/vapours/spray.  
P262 - Do not get in eyes, on skin, or on clothing.  
P263 - Wash contaminated clothing before reuse.  
P264 - Wash hands thoroughly after handling.  
P270 - Do not eat, drink, or smoke when using this product.  
P271 - Use only outdoors or in a well-ventilated area.  
P272 - Contaminated work clothing should not be allowed out of the workplace.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, eye protection or face protection.  
P284 - In case of inadequate ventilation wear respiratory protection.

**Response**

: P314 - Get medical advice or attention if you feel unwell.  
P362 - Take off contaminated clothing and wash before reuse.  
P301+310 - IF SWALLOWED: Immediately call a POISON CENTER or physician.  
P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P302+352 - IF ON SKIN: Wash with plenty of water.  
P303+361+353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.  
P332+313 - If skin irritation occurs get medical advice/attention.  
P337+313 - If eye irritation persists get medical advice/attention.  
P362+364- Take off contaminated clothing and wash it before reuse.  
P337+313 - If eye irritation persists get medical advice/attention.  
P370+380 - In case of fire: Evacuate area.

- Storage** : P410 - Protect from sunlight.  
P402+404 - Store in a dry place. Store in a closed container.  
P403+235 - Store in a well-ventilated place. Keep cool.
- Disposal** : P501 - Dispose of contents/containers in accordance with local regulation
- Other hazards which do not result in classification** : None identified.
- SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS**
- Substance/mixture** : Mixture
- Other means of identification** : The base component of the premium quality dual pack strontium chromate epoxy primer.
- CAS number/other identifiers**
- CAS number** : Not applicable.

Ingredient name	CAS number	%	UN GHS Classification
Toluene	108-88-3	20.0-25.0	Flam. Liq. 2, H225 Acute Tox. 4, H332 Acute Tox. 5, H303 Skin Irrit. 2, H315 Eye Irrit. 2B, H320 Rep. Tox. 2, H361d
Ethanol	64-17-5	15.0-20.0	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Eye Irrit. 2, H319 Skin Irrit. 2, H315
Fatty acids, tall-oil, reaction products with diethylenetriamine	61790-69-0	5.0-10.0	Skin Irrit. 2, H315 Eye Irrit. 2, H319
Strontium Chromate	7789-06-2	5.0-10.0	Canc. 2B, H350 Aquatic Acute, 2, H400 Aquatic Chronic, 1, H410 Acute Tox. 4, H301
Reaction product: Bisphenol A-(epichlorohydrin)	25068-38-6	5.0-10.0	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic. 2, H411

Ingredient name	CAS number	%	UN GHS Classification
Xylene	1330-20-7	2.0-5.0	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319
Methyl ethyl ketone	78-93-3	2.0-5.0	Flam. Liq. 2, H225 Eye Irrit. 2, H319 Skin Irrit. 2, H315 STOT SE 3, H336
Isopropyl alcohol	67-63-0	2.0-5.0	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

#### SECTION 4: FIRST AID MEASURES

##### Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation persist.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	: Remove contaminated clothing and shoes. Wash contaminated skin with soap or a recognised skin cleaner and plenty of water. Avoid the use of solvents. Get medical attention if symptoms persist. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Remove victim to fresh air and keep at rest in a position Comfortable for breathing. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so



by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe.

### Most important symptoms/ effects, acute and delayed

#### Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: Toxic if inhaled. May cause drowsiness or dizziness.
Skin contact	: Toxic in contact with skin. Causes skin irritation.
Ingestion	: Toxic if swallowed.

#### Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may include pain or irritation, watering or redness.
Inhalation	: Adverse symptoms may include nausea or vomiting, headache, drowsiness/ fatigue, or dizziness/vertigo, unconsciousness, reduced fetal weight, increase in fetal deaths skeletal malformations.
Skin contact	: Adverse symptoms may include irritation or redness.
Ingestion	: Toxic if swallowed.

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first aiders	: No action shall be taken involving any personal risk or without Suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## SECTION 5: FIRE-FIGHTING MEASURES

### Extinguishing media

Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire such as dry powder, CO <sub>2</sub> , water spray (fog) or foam. Use fog to cool and control.
------------------------------	--





Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face piece operated in positive pressure mode.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment, and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk-through spilled material. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with



soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil, or air).

## Methods and materials for containment and cleaning up

- Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose via a licensed waste disposal contractor.
- Large spill : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non combustible, absorbent material e.g., sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

## SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

- : Put on appropriate personal protective equipment (see Section 8). Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored, and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Store and use away from heat, sparks, open flame, or any other ignition source. Use explosion-proof electrical (ventilating, lighting and





STEELTECT 1500 SB

(AW 255)

UN1263 PAINT

Safety Data Sheet

Date of Issue: 30/08/2022 Revision Date 30/08/2022 | Version 9.0

material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool, and well ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Do not reuse container.

## SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure limits

<b>Ingredient name</b>	<b>Exposure limits</b>
Ethanol	<b>OHSA:</b> TWA: OEL-RL: 1000 ppm; 1900 mg/m <sup>3</sup>
1-Methoxy-2-propanol	<b>ACGIH (USA):</b> TWA: 100 ppm; STEL: 300 ppm
Isopropyl alcohol	<b>ACGIH (USA):</b> TWA: 400 ppm; STEL: 200 ppm

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Appropriate engineering controls

: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters, or engineering modifications to the process



equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

#### Hygiene measures

: Wash hands, forearms, and face thoroughly after handling chemical products, before eating, smoking, and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

: Avoid direct contact. Never touch eyes with dirty hands or gloves. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

#### Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be always worn when handling chemical products if a risk assessment indicates this is necessary.

#### Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Respiratory protection

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary e.g., in case of insufficient ventilation. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Physical state	: Liquid
Colour	: Light straw
Odour (Threshold)	: No data available
Melting point	: Not applicable
Boiling point	: No data available
Flammability (gas, liquid, solid)	: No data available
Lower and upper explosive (flammable) limits	: No data available
Flash point	: < 12 °C
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
pH	: Not applicable
Viscosity	: No data available
Solubility	: No data available
Partition coefficient, n-octanol/water	: No data available
Evaporation rate	: No data available
Vapour pressure	: No data available
Relative density	: 0.93 g/ml (typical)
Vapour density	: No data available



STEELTECT 1500 SB

(AW 255)

UN1263 PAINT

Safety Data Sheet

Date of Issue: 30/08/2022 Revision Date 30/08/2022 | Version 9.0

**SECTION 10: STABILITY AND REACTIVITY**

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions: : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**SECTION 11: TOXICOLOGICAL INFORMATION****Acute Toxicity**

<b>Ingredient name</b>	<b>Result</b>	<b>Species</b>	<b>Dose</b>	<b>Exposure</b>
Ethanol	LC50 Inhalation Vapor LD50 Oral	Rat Rat	124700 mg/m <sup>3</sup> 7 g/kg	4 hours -
Benzenesulfonic acid, mono-C10-13-alkyl derivs., sodium salts	LC50 Dermal LD50 Oral LD50 Oral	Rat Rat Mouse	> 1000 mg/kg 1086 - 1980 mg/kg 2250 mg/kg	- - -
-Methoxy-2-propanol	LD50 Oral LD50 Dermal LD50 Inhalation	Rat Rabbit Rat	4016 mg/kg > 2000 mg/kg > 25.8 mg/l	- - 6 hours
Isopropyl alcohol	LC50 Oral LC50 Inhalation LD50 Dermal	Rat Rat Rabbit	3437 ppm 72.6 mg/l 4059 mg/kg	- 4 hours -

Irritation/Corrosion  
No data Available

**Specific target organ toxicity (single exposure)**

<b>Ingredient name</b>	<b>Category</b>	<b>Route of exposure</b>	<b>Target Organs</b>
Isopropyl alcohol	Category 3	Not determined	Kidneys

Specific target organ toxicity (repeated exposure)  
No data available

Aspiration hazard  
No data available

Information on the likely routes of exposure : Inhalation, skin, and eye contact.

Potential acute health effects

Eye contact : Causes serious eye damage.  
Inhalation : Toxic if inhaled. May cause drowsiness or dizziness.

Skin contact : Toxic in contact with skin. Causes skin irritation.  
Ingestion : Toxic if swallowed.

Symptoms related to the physical, chemical, and toxicological characteristics

Eye contact : Adverse symptoms may include pain or irritation, watering or redness.

Inhalation : Adverse symptoms may include nausea or vomiting, headache, drowsiness/ fatigue, or dizziness/vertigo.

Skin contact : Adverse symptoms may include irritation or redness.  
Ingestion : Adverse symptoms may include nausea or vomiting.

Potential Chronic health effects

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Acute toxicity estimates

No data available

## SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ingredient name	Result	Species	Exposure
Toluene	Acute LC50 8.1 mg/l Fish	Salmon	96 hours
	Acute EC 6.00 mg/l Aquatic	Daphnia magna	48 hours
	Acute EC50 9.4 mg/l Algae	Green algae	8 hours
Ethanol	Acute LC50 13000 mg/l Fish	Trout	96 hours
	Acute LC50 15300 mg/l Fish	Fathead minnow	48 hours
	Acute LC50 250ppm Fish	Goldfish	8 hours



STEELTECT 1500 SB

(AW 255)

UN1263 PAINT

Safety Data Sheet

Date of Issue: 30/08/2022 Revision Date 30/08/2022 | Version 9.0

Ingredient name	Result	Species	Exposure
Xylene	Acute LC50 8500 ug/l Aquatic Acute LC50 3300 to 4093 ug/l Fish	Crustaceans - Palaemonetes Pugio Oncorhynchus mykiss - 0.6 g	48 hours 96 hours
Methyl ethyl ketone	Acute LC50 5640 mg/l Fish Acute LC50 1950 mg/l Aquatic Acute EC50 10000-20000 ppm Acute EC50 100-10000 ppm Acute EC50 3000-10000 mg/l, Algae	Bluegill sunfish Brine shrimp ASRI Test Growth Inhibition Test Algal growth Inhibition test	24 hours 24 hours - - -
Isopropyl alcohol	Acute LC50 6550 mg/l Fish Acute EC50 13299 mg/l Organic Acute EC50 >1000 mg/kg Algae	Pimephales promelas Daphnia magna Scenedesmus subspicatus	96 hours 48 hours 96 hours

## Persistence and degradability

Ingredient name	Aquatic half-life	Photolysis	Biodegradability
Toluene	-	-	Readily
Xylene	Fresh water <28 days	1 to 2 day(s)	-
Methyl ethyl ketone	BOD5: 1515-1.92 mg/l in 5 days (Std dilution technique, normal sewage seed) COD: 2.2-2.31 mg/l BOD 6% in 28 days (CO2 Evolution Test)	- - -	Highly biodegradable in aerobic systems using activated sludge and sewage seed

## Bio accumulative potential

Ingredient name	LogPow	BCF	Potential
Toluene	-	<100	-
Xylene	3.12	20	Low
Methyl ethyl ketone	0.29	-	Low

## Mobility in soil

Soil/ water partition  
coefficient (KOC)

: No data available.

## Mobility

PBT/vPvB data

: No data available.

: P: No data available.

B: No data available.

T: No data available.






Other adverse effects : No known significant effects or critical hazards.

### SECTION 13: DISPOSAL CONSIDERATIONS

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions, and any by-products should always comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### SECTION 14: TRANSPORT INFORMATION

	Transportation - road - SANS 10228:2012	Transportation- Maritime - IMO/ IMDG	Transportation- Air – IATA
UN number	1263	1263	1263
UN proper shipping name	Paint	Paint	Paint
Transport hazard class(es)	3 	3 	3 
Packing group	III	III	III
Environmental Hazards	No	No	No
Additional information	No data available	Emergency schedules (EmS) F-E, S-E	Passenger and Cargo Aircraft Ltd QTY: Quantity limitation: 1 L Packaging instructions: Y341



STEELTECT 1500 SB

(AW 255)

UN1263 PAINT

Safety Data Sheet

Date of Issue: 30/08/2022 Revision Date 30/08/2022 | Version 9.0

			<b>Passenger and Cargo Aircraft:</b> Quantity limitation: 5 L Packaging instructions: 353 <b>Cargo Aircraft Only:</b> Quantity limitation: 60 L Packaging instructions: 364
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	No data available	No data available	No data available

## SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product

: Relevant information regarding authorization: Occupational Health and Safety Act 1993 Regulation for Hazardous Chemical Substances. Relevant information regarding restrictions: None known. EU regulations: Regulation EC 1272/2008 [EU-GHS/CLP] and EU directives 67/548/EEC or EC 1999/45/EC Other National regulations: None. Standards used for PPE recommendations in Section 8: NIOSH-National Institute for Occupational Health and Safety (USA) EN 166 European standard which concerns the area of eye protection. EN 374-3 European standards for permeation and penetration. EN 141/EN 143 European standards for gas mixtures to remove specified gases and vapours or combined filters for removing solids, and/or liquid particles and specified gases and vapours.

## SECTION 16: OTHER INFORMATION

### History

Date of review : 30/08/2022

Date of review	Version	Amendments
30/08/2022	9.0	GHS compliant SDS
19/07/2018	8.0	-

Date of previous issue : 19/07/2018



STEELTECT 1500 SB

(AW 255)

UN1263 PAINT

Safety Data Sheet

Date of Issue: 30/08/2022 Revision Date 30/08/2022 | Version 9.0

#### Key to abbreviations

: ATE = Acute Toxicity Estimate  
BCP Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL 73/78 = International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
OHSA = Occupational Health and Safety Act, 1993 (South Africa)  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
UN = United Nations

#### References

: Supplier Safety Data Sheets.

#### Further information:

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

#### Notice to readers:

Employers should use this information only as a supplement to other information gathered by them and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

#### Legal disclaimer:

The above information is believed to be correct but does not purport to be all inclusive and shall be only used as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.