


TECHNICRETE Double Roman & Tuscan Roof Tiles
cost effectiveness with aesthetic appeal

ANTIQUE COLOUR

(CODE:)



GRANULAR FINISHED

Granular finish only available in Polokwane

(CODE:)



SMOOTH COLOUR

(CODE:)



Tuscan Roof Tiles



Colours shown may vary from the true colour due to the printing process.

Technicrete reserves the right to change or amend the contents of this document at anytime without any notice with this document intended for general information only. Any specific information required about product specifications, applications, technical information, sales conditions, warranties and guarantees as required for any design or installation should be obtained from Technicrete.



Technicrete House
Cnr. Main Reef Road & Houtkapper Street, Roodepoort, 1725
Tel: 011 674 6900 – Fax: 011 672 1425
Email: info@technicrete.co.za
www.technicrete.co.za
0861 266267

Branches:
White River: 013 750-0319
Polokwane: 015 298-8083


TECHNICRETE
Double Roman,
& Tuscan Roof Tiles

Cost effectiveness with aesthetic appeal

Technicrete Double Roman & Tuscan Roof Tiles, the high quality roof coverings to enhance any building construction. Available in an exciting range of colours and finishes.



Technicrete
Tuscan



Technicrete
Double Roman









TECHNICRETE
quality support


PAVING • SPECIAL PRODUCTS • **CONCRETE ROOF TILES** • KERBS • MASONRY • SHOTCRETES
EROSION PROTECTION BLOCKS • MINING • TRAFFIC CALMING BLOCK • PREBAGGED PRODUCTS
PRECAST PRODUCTS • RETAINING WALLS • STOPE SUPPORT SYSTEMS • HEAVY DUTY PAVEMENTS






Nailing

The first two tiles at verges, eaves, hips, valleys and abutments must be nailed. It is recommended that every third tile in every third course be nailed, over 45° roof pitch and in exposed areas every tile should be nailed.



TILING DATA	Pitch 17.5 to 25	Pitch 26 & above	
Tile head lap (minimum)	100 mm	75 mm	<div>Technicrete Double Roman</div> 
Batten centres (maximum)	320 mm	345 mm	
Length of battens per m² (average)	3.15 m	2.99 m	
Tiles per m² (average)	10.42	9.66	
Mass of tiles per m² (average)	50 kg	46 kg	
Size of tile	420 x 330 mm	420 x 330 mm	
Mass per tile (approx)	4.8 kg	4.8 kg	<div>Technicrete Tuscan</div> 
Underlay	Mandatory	Recommended	



	Accessories	Weight	No. per meter	Note
	Tapered ridge tile	4.7 kg	2.5	
	Angle butt ridge tile	4.5 kg	3	
	Butt mono ridge	6.3 kg	3	
	Angle collar ridge	4.5 kg	3	
	Hip starter	3.9 kg	N/A	N/A