

TEST RESULTS

THERMAL TEST RESULTS - SANS 204		MECHANICAL PERFORMANCE TEST RESULTS - SANS 613		
DESCRIPTION	RESULTS	DESCRIPTION	RESULTS	
U-VALUE	6.51 W/m²/K	NEGATIVE PRESSURE	Passed 1500 PA	
SHGC	0.613	POSITIVE PRESSURE	Passed 1500 PA	
DESIGN WIND LOAD	1500 PA	WATER PENETRATION	Passed 300 PA	
6.38 mm Laminated Safety Glass		STRUCTURAL	Passed 2250 PA	

Test results are based on a specific window size and configuration and results will differ for different window sizes and configurations. Refer to U-Solve for actual design results.

APPLICATIONS

CREALCO				
Icon sliding door	\checkmark			
Rouge sliding door	\checkmark			
Palace high performance sliding door	√	√	√	
4500 sliding door		√	√	√
Clip 38 sliding door		√	√	√
Clip 44 internal sliding door			\checkmark	
Vistafold sliding folding door		√	\checkmark	\checkmark
5000 top hung sliding folding door		√	\checkmark	\checkmark
Serene heavy duty tilt & sliding door				


Crealco product range is available from the following Wispeco Appointed Stockists:



This brochure must be read in conjunction with the Installation, Cleaning & Maintenance Guidelines for the relevant system.

The manuals must also be used in conjunction with the design and cutting lists from the latest version of StarFront.





crealco ICON™

crealco ICON™

TYPICAL CONFIGURATIONS

The Crealco Icon[™] sliding door is a tried and tested domestic patio door which has been on the market for several years.

A reliable, sliding door with quality hardware designed for a 2, 3, 4, or 6 panel configuration.

Overall, the Crealco Icon[™] is an excellent performing patio door.

FEATURES

- Available with casement window sidelight options.
- Can accommodate fly screens.
- Easy to install and low maintenance.
- Good thermal U-values of less than 7 W/m²/K
- Various lock options available.

GLAZING

• Suitable for single glazing up to 6.38 mm laminated safety glass.

GASKET & SEALS

- High quality, locally available gaskets and seals are available.
- Affordable and reliable.

FINISH


• Available in a variety of popular architectural powder coating colours and finishes.

HARDWARE

- All hardware is locally available and of high quality.
- Suitable for coastal regions

This brochure must be read in conjunction with the Installation, Cleaning & Maintenance Guidelines for the relevant system.

The manuals must also be used in conjunction with the design and cutting lists from the latest version of StarFront









Crealco Icon[™] sliding door cross-section



The manuals must also be used in conjunction with the design and cutting lists from the latest version of StarFront.