

SPECIFICATION

THERMAL INFORMATION		TEST PERFORMANCE RESULTS	
DESCRIPTION	RESULTS	DESCRIPTION	RESULTS
U-VALUE	2.84 W/m²K	NEGATIVE PRESSURE	2500 PA
SHGC	0.60	POSITIVE PRESSURE	2500 PA
DESIGN WINDLOAD	2500 PA	WATER PENETRATION	500 PA
25mm DOUBLE GLAZING IGU		STRUCTURAL	3750 PA

*Test results were achieved based on a specific design configuration and size and may differ for other configurations and sizes.


APPLICATIONS

CREALCO				
sliding folding doors	HOME	MANSION	MALL	TOWER
Facade 60 curtain wall system			✓	✓

Crealco product range available from the following Wispeco Appointed Stockist:



This manual must be read in conjunction with the Installation, Cleaning & Maintenance Document and Performance Certificates for the relevant system. The manual must also be used in conjunction with the design and cutting list from the latest version of Starfront.



The Crealco Façade 60 curtain wall system is the latest cutting-edge product to be added to the Crealco product range. The Crealco Façade 60 is a remarkable, high-performance curtain wall system, providing manufacturers the flexibility to fabricate high-performance building solutions.

The Façade 60 is uniquely designed for the South African market, with outstanding thermal efficiency properties.

FEATURES

- Thermally efficient, thus reducing building costs
- Accommodates window and door inserts
- Designed for easy manufacturing
- All aluminium and hardware components are locally available
- Minimal machining required, due to pre-punched profiles
- Unique mullion jig to fit transoms

GLAZING

- Designed for both single and double glazing combinations
- Can accommodate up to 10.38 mm for single glazing

GASKET & SEALS

- Locally available
- Inflex (EPDM equivalent)
- Only 3 gaskets required for both single and double glazing

FINISH

- Both standard and non-standard colours available (SABS approved)
- Anodised (15 Mic) for inland
- Anodised (25 Mic) for coastal

HARDWARE

- Minimal fittings and hardware required
- Locally available
- Stainless steel fixings


Exciting new hardware component - Spigot Clamp



TYPICAL CONFIGURATIONS



Front view of the system



Rear view of the system



This manual must be read in conjunction with the Installation, Cleaning & Maintenance Document and Performance Certificates for the relevant system. The manual must also be used in conjunction with the design and cutting list from the latest version of Starfront.

This manual must be read in conjunction with the Installation, Cleaning & Maintenance Document and Performance Certificates for the relevant system. The manual must also be used in conjunction with the design and cutting list from the latest version of Starfront.