

PRODUCT DATA SHEET



OPC IS AN ORDINARY PORTLAND CEMENT THAT IS IDEAL FOR A BROAD RANGE OF APPLICATIONS IN THE CONSTRUCTION, BUILDING, READYMIX, PRECAST AND CONCRETE PRODUCT MANUFACTURING INDUSTRIES.

PRODUCT DESCRIPTION:

OPC is made from high quality raw materials. The clinker is interground with gypsum to control setting. Grinding is carefully controlled to ensure consistent performance in the 42,5N strength class.

APPLICATIONS:

OPC has been engineered to achieve cost effective concrete and concrete products. Applications include concrete, grouts, shotcrete, precast products, masonry products and specialist applications. It can also be used in mortar or plaster mixes.

OPC is most suited for blending with extenders such as fly ash and ground granulated blastfurnace slag (GGBS). It is also compatible with commercial chemical admixtures.

SPECIFICATIONS:

OPC is manufactured to SANS 50197-1 for Common Cements in the 42,5N strength class, and is identified as:

- Portland Cement CEM I 42,5N.

This product is in line with requirements given in the NHBRC manual.

STORAGE:

Bulk storage silos should be inspected on a regular basis to ensure that the inspection hatch seal is watertight and filters are clean and unblocked.

Cement bags are not weatherproof and should be stored under cover, off the ground to a maximum height of 12 bags.

HANDLING & SAFETY:

Refer to PPC Cement Safety Data Sheet, obtainable from PPC.

SUPPLY:

OPC is available nationally from all PPC factories and most depots except De Hoek. Please check with your local sales office for further details.

OPC

PRICE:

PPC Cement sales can be contacted for delivered prices. Contact details are provided below:

JOHANNESBURG

P O Box 40073 Cleveland 2022
Tel: 011 626 3150
Fax: 011 626 2560

CAPE TOWN

P O Box 268, Milnerton 7435
Tel: 021 550 2100
Fax: 021 550 2111

GEORGE

P O Box 4961 George East 6539
Tel: 044 871 3024
Fax: 044 871 3076

NELSPRUIT

P O Box 7888 Sonpark Nelspruit 1200
Tel: 013 741 4140
Tel: 013 741 4142

PPC BOTSWANA

P O Box 2424 Gaborone Botswana
Takatokwane Way Gaborone West Industrial Sites
Tel: (267) 390 1553
Fax: (267) 393 9393

PIETERMARITZBURG

P O Box 28488 Haymarket 3200
Tel: 033 386 6171
Fax: 033 386 3545

POLOKWANE

P O Box 55491 Polokwane 0700
Tel: 015 297 2503/1826/0965
Fax: 015 297 5372

RUSTENBURG

P O Box 20570 Protea Park
Rustenburg 0305
Tel: 014 597 0100
Fax: 014 597 0115

PORT ELIZABETH

Private Bag X2016 North End
Port Elizabeth 6056
Tel: 041 486 2272
Fax: 041 486 2145



PPC
CEMENT

Web site: <http://www.ppc.co.za>

TECHNICAL INFORMATION:

Typical technical data is supplied below. Further technical information can be obtained from the PPC Cement help line, toll-free, on 0800-023-470. PPC has comprehensively equipped chemical, cement and concrete laboratories and can supply specific information and assistance regarding cement and concrete technology.

Mix designs are offered as a service to customers.

TYPICAL PROPERTIES:

Chemical Composition	Typical OPC results for the PPC group	SANS 50197-1 CEM I 42,5N
Insoluble residue: %	2,0	5,0 maximum
Sulphur Trioxide: %	2,0	3,5 maximum
Loss on Ignition: %	2,5	5,0 maximum
Chloride: %	<0,01	0.1 maximum

All % calculated by mass.

Physical Properties	Typical OPC results for the PPC group	Specification requirements SANS 50197-1 Class 42,5N
Setting Times: Initial: Minutes Final: Hours	125 2,5	60 minimum -
Specific Surface (Blaine): m ² /kg Fineness: Residue on 212 µm screen: %	380 0	- -
Soundness: Le Chatelier Expansion: mm	1	10 maximum
Typical motar prism results determined in accordance with EN 196-1 Early strength requirement at 2 days (MPa) Standard strength at 28 days (MPa)	±23 ±52	≥10 ≥42,5 ≤62,5
Densities: Relative density Loose bulk density: kg/m ³ Bulk density: kg/m ³	3,14 1300 1500	
Approximate Volumes: 50kg bag: ℓ	±33	

Please contact our toll free help line if actual figures are required.

IMPORTANT NOTE: The information and/or specifications contained herein are given in good faith as being true and accurate but no liability is accepted by PPC, its employees, distributors, representatives or agents, for any loss or damage, direct or indirect, resulting from using the information, following the specifications or adopting recommendations and/or suggestions as actual conditions of use are beyond its control.
This data sheet was published in November 2006

OPC