

Vitacon has the unusual feature of having a diamond mesh serrated pattern, giving excellent non-slip characteristics and in it's completed form, offering a lightweight, but strong section, ideal for use in conveyor walkways, inclines or where slip resistant floors are required. Supplied in standard 750mm long by 250mm wide sections, this offers the potential designer easy-to-use increments to obtain optimum utilisation for a modular fitting floor area. These sections may be bolted together, laid side by side and welded at intervals inside the angle frames making the installation a breeze and which give a continuous floor appearance with no loss of grip at all.

Materials in which this product is manufactured in, are mild steel and aluminium only. Aluminium loadings are available on request.

Vitacon Loading Table

	Spans in mm		
	500	750	1000
U	3565	1580	885
d	0.94	1.41	1.88
C	881	592	442
d	0.38	0.85	1.51

Panel width = 250mm

Mass = 6.4kg/m

Vitacon Dimple Floor has been developed for a specific consumer market where industrial serrated surfaces are too aggressive for the application required. Vitacon Dimpled floor offers the same advantages as the Vitacon Serrated floor without the severe aggressive surface. As can be seen from the picture, this product is ideal for storage flooring, shelving or racking walkways requiring the passage of wheeled trolleys, building sites, control room floors and many other similar applications where a firm grip is required underfoot. The product is manufactured in two widths of 250mm or 300mm in 6m lengths with standard raised perforations as shown.

