

Walcro®



Toilet Flushing Valves

WALCRO 550 Toilet Flushing Valves - Back or Top entry models

WALCRO 550

Inlet:

Ø 20mm BSP, Female

Maintained pressure:
100kPa to 600kPa

Installation:

Exposed, chrome

SABS, Jaswic, DZR Brass,
made in S.A.



WALCRO 550B

Back entry pipe model.



WALCRO 550T

Top entry pipe model.



WALCRO 103LC Toilet Flushing Valves - Concealed entry models

WALCRO 103LC

Inlet:

Ø 20mm BSP, Female

Maintained pressure:
100kPa to 600kPa

Installation:

Concealed, duct

SABS, Jaswic, DZR Brass,
made in S.A.



WALCRO 103LC

Concealed with standard
Push button assembly.



WALCRO 103LCXP

Concealed with upmarket
XP Push button assembly.



WALCRO 106 Toilet Flushing Valves - Back or Top entry models

WALCRO 106

Inlet:

Ø 25mm BSP, Female

Maintained pressure:
30kPa to 600kPa

Installation:

Exposed, chrome

SABS, Jaswic, DZR Brass,
made in S.A.



WALCRO 106B

Back entry pipe.



WALCRO 106T

Top entry pipe.



WALCRO 106C Toilet Flushing Valves - Concealed entry models

WALCRO 106C

Inlet:

Ø 25mm BSP, Female

Maintained pressure:
30kPa to 600kPa

Installation:

Concealed, duct

SABS, Jaswic, DZR Brass,
made in S.A.



WALCRO 106C

Concealed with standard
Push button assembly.



WALCRO 106CXP

Concealed with upmarket XP
Push button assembly.



Walker Croswell

Walker Croswell (Pty) Ltd PO Box 1018, Bromhof, 2154.
Walcro House, Bush Hill Office Park, Rachelle Close,
Ostrich Road (corner Hawken), Bromhof,
Randburg, Gauteng, South Africa.
Telephone: 011 793-1031 Fax: 011 793-1092
Cape Town: 021 797-4327 or Cell: 072 821 4463
e-mail: walcro@iafrica.com Website: www.walcro.co.za

Walcro®



Toilet Flushing Valves

WALCRO 104 Toilet Flushing Valves - Back or Top entry models

WALCRO 104

Inlet:

Ø 25mm BSP, Female
Ø 32mm available on request

Maintained pressure:

30kPa to 600kPa

Installation:

Exposed, chrome

SABS, Jaswic, DZR Brass,
made in S.A.

Featuring telescopic
adjustment and
non-return/isolating valve.



WALCRO 104B

Back entry pipe model.



WALCRO 104T

Top entry pipe model.



WALCRO 104C Toilet Flushing Valves - Concealed entry models

WALCRO 104C

Inlet:

Ø 25mm BSP, Female
Ø 32mm available on request

Maintained pressure:

30kPa to 600kPa

Installation:

Concealed, duct

SABS, Jaswic, DZR Brass,
made in S.A.

Featuring telescopic
adjustment and
non-return/isolating valve.



WALCRO 104C

Concealed with standard Push button assembly.



WALCRO 104CXP

Concealed with upmarket XP Push button assembly.



WALCRO 107LP (Low pressure) Toilet Flushing Valves - "Built-in" model

WALCRO 107LP

Inlet:

Ø 25mm BSP, with union

Maintained pressure:

30kPa to 600kPa

Installation:

Front access valve for building in
with stainless steel cover.

SABS, Jaswic, DZR Brass,
made in S.A.



WALCRO 107HP (High pressure) Toilet Flushing Valves - "Built-in" model

WALCRO 107HP

Inlet:

Ø 20mm BSP, with union

Maintained pressure:

100kPa to 600kPa

Installation:

Front access valve for building in
with stainless steel cover.

SABS, Jaswic, DZR Brass,
made in S.A.



WALCRO Flushvalve features

All Walcro flushing valves feature the following for extended reliability and the ultimate in control.

- Manufactured locally from DZR Brass.
- Integral vacuum breakers prevent back-siphoning (WC).
- Flow rates and flush time adjustable.
- Complies with SABS and JASWIC.
- Guaranteed for 12 months.
- All working parts housed in a sturdy, easily removable engineering plastic cartridge for hassle free maintenance.

Walcro concealed XP upmarket push button



Walker Croswell

Walker Croswell (Pty) Ltd PO Box 1018, Bromhof, 2154.
Walcro House, Bush Hill Office Park, Rachelle Close,
Ostrich Road (corner Hawken), Bromhof,
Randburg, Gauteng, South Africa.
Telephone: 011 793-1031 Fax: 011 793-1092
Cape Town: 021 797-4327 or Cell: 072 821 4463
e-mail: walcro@iafrica.com Website: www.walcro.co.za

Walcro®



Walcro Special Application Toilet Flushing Valves

Extended lever models - Users with limited hand use

Selected **Walcro** exposed toilet flushing valves are available with an extended lever for ease of operation for persons with limited hand use.

Please specify if a back or top entry pipe is required.



WALCRO 103LH
20mm inlet toilet flushvalve
NB: For right hand side activation only



WALCRO 104H
25mm inlet toilet flushvalve
BEST CHOICE Can alternate for left and right hand side use

WALCRO Squat pan toilet flushing valves for Eastern applications

WALCRO 550SP

Application: Squat Pan Toilets
Inlet: Ø 20mm BSP, Female
Maintained pressure: 100kPa to 600kPa
Installation: Exposed chrome with extended pipe

SABS, Jaswic, DZR Brass, made in S.A.



WALCRO 106SP

Application: Squat Pan Toilets
Inlet: Ø 25mm BSP, Female
Maintained pressure: 30kPa to 600kPa
Installation: Exposed chrome with extended pipe

SABS, Jaswic, DZR Brass, made in S.A.



WALCRO Prison & Police Cell products for Toilet Flushing Valves

Walcro prison type push button for use with concealed Walcro toilet flushing valve in prison, police cell or high vandalism projects. Please specify prison type push button when ordering any of the Walcro concealed toilet valves.



For prisons

Walcro compression/solder adaptor for prison type stainless steel toilet pans.



**Walcro 103LC,
Walcro 106C & 104C**

Walker Croswell

Walker Croswell (Pty) Ltd PO Box 1018, Bromhof, 2154.
Walcro House, Bush Hill Office Park, Rachelle Close,
Ostrich Road (corner Hawken), Bromhof,
Randburg, Gauteng, South Africa.
Telephone: 011 793-1031 Fax: 011 793-1092
Cape Town: 021 797-4327 or Cell: 072 821 4463
e-mail: walcro@iafrica.com Website: www.walcro.co.za